



Model: HGST HUH721212AL
S/N: 5QGH5W1F



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HGST HUH721212AL**

Serial: **5QGH5W1F**

Size(Apparent): **12 TB, 12000138625024 bytes**

Bus: **ATA**

Size(Real): **12 TB, 12000138625024 bytes**

Disk Erasure Details

Start time: **2025/02/22 17:16:13**

End time: **2025/02/25 04:26:07**

Duration: **59:09:54**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **12000138625024, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **169 MB/sec**

Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HGST HUH721212AL
S/N: 5QGH5W1F



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

model family: HGST Ultrastar DC HC520 (He12)
device model: HGST HUH721212ALE600
serial number: 5QGH5W1F
lu wwn device id: 5 000cca 2b0c6e79c
firmware version: LEGNT925
user capacity: 12,000,138,625,024 bytes [12.0 TB]
sector sizes: 512 bytes logical, 4096 bytes physical
rotation rate: 7200 rpm
form factor: 3.5 inches
device is: In smartctl database [for details use: -P show]
ata version is: ACS-2, ATA8-ACS T13/1699-D revision 4
sata version is: SATA 3.2, 6.0 Gb/s (current: 6.0 Gb/s)
local time is: Tue Feb 25 04:26:10 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled

=== start of read smart data section ===

smart overall-health self-assessment test result: PASSED

general smart values:

offline data collection status: (0x84)Offline data collection activity
was suspended by an interrupting command from host.
auto offline data collection: Enabled.
self-test execution status: (0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: (87) seconds.
offline data collection
capabilities: (0x5b) SMART execute Offline immediate.
auto offline data collection on/off support.
suspend offline collection upon new
command.
offline surface scan supported.
self-test supported.
no conveyance self-test supported.
selective self-test supported.
smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability: (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: (2) minutes.
extended self-test routine
recommended polling time: (1313) minutes.
sct capabilities: (0x003d)SCT Status supported.
sct error recovery control supported.
sct feature control supported.
sct data table supported.

smart attributes data structure revision number: 16

vendor specific smart attributes with thresholds:

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x000b	100	100	016	pre-fail	always	-	0
2	throughput_performance	0x0005	130	130	054	pre-fail	offline	-	100
3	spin_up_time	0x0007	178	178	024	pre-fail	always	-	382 (average 357)
4	start_stop_count	0x0012	100	100	000	old_age	always	-	12
5	reallocated_sector_ct	0x0033	100	100	005	pre-fail	always	-	0
7	seek_error_rate	0x000b	100	100	067	pre-fail	always	-	0



Model: HGST HUH721212AL

S/N: 5QGH5W1F



Disk Erasure Report

Page 3 - Smart Data

8	seek_time_performance	0x0005	140	140	020	pre-fail	offline	-	15
9	power_on_hours	0x0012	098	098	000	old_age	always	-	18793
10	spin_retry_count	0x0013	100	100	060	pre-fail	always	-	0
12	power_cycle_count	0x0032	100	100	000	old_age	always	-	12
22	helium_level	0x0023	100	100	025	pre-fail	always	-	100
192	power-off_retract_count	0x0032	100	100	000	old_age	always	-	789
193	load_cycle_count	0x0012	100	100	000	old_age	always	-	789
194	temperature_celsius	0x0002	171	171	000	old_age	always	-	35 (min/max 19/37)
196	reallocated_event_count	0x0032	100	100	000	old_age	always	-	0
197	current_pending_sector	0x0022	100	100	000	old_age	always	-	0
198	offline_uncorrectable	0x0008	100	100	000	old_age	offline	-	0
199	udma_crc_error_count	0x000a	200	200	000	old_age	always	-	0

smart error log version: 1
no errors logged

smart self-test log structure revision number 1
no self-tests have been logged. [to run self-tests, use: smartctl -t]

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.
if selective self-test is pending on power-up, resume after 0 minute delay.