



Model: SEAGATE ST4000NM0063

S/N: Z1Z96GGW0000R601SDBH

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST4000NM0063**

Serial: **Z1Z96GGW0000R601SDBH**

Size(Apparent): **4000 GB, 4000787030016 bytes**

Bus: **SAS**

Size(Real): **4000 GB, 4000787030016 bytes**

## Disk Erasure Details

Start time: **2025/02/24 14:58:34**

End time: **2025/02/25 16:47:18**

Duration: **25:48:44**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **4000787030016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **129 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST4000NM0063

S/N: Z1Z96GGW0000R601SDBH

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST4000NM0063  
revision: 0004  
compliance: SPC-4  
user capacity: 4,000,787,030,016 bytes [4.00 TB]  
logical block size: 512 bytes  
lu is fully provisioned  
rotation rate: 7200 rpm  
form factor: 3.5 inches  
logical unit id: 0x5000c50083f666eb  
serial number: Z1Z96GGW0000R601SDBH  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Tue Feb 25 16:47:20 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C  
drive trip temperature: 60 C

accumulated power on time, hours:minutes 63820:21  
manufactured in week 32 of year 2015  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 155  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 2808  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 3017190371  
blocks received from initiator = 1538248043  
blocks read from cache and sent to initiator = 2461651968  
number of read and write commands whose size <= segment size = 2046809344  
number of read and write commands whose size > segment size = 146017

vendor (seagate/hitachi) factory information

number of hours powered up = 63820.35  
number of minutes until next internal smart test = 14

error counter log:

|         | errors corrected by<br>ecc | fast   delayed | rereads/<br>rewrites | total<br>errors<br>corrected | correction<br>algorithm<br>invocations | gigabytes<br>processed<br>[10^9 bytes] | total<br>uncorrected<br>errors |
|---------|----------------------------|----------------|----------------------|------------------------------|----------------------------------------|----------------------------------------|--------------------------------|
| read:   | 2141152390                 | 0              | 0                    | 2141152390                   | 0                                      | 517069.718                             | 0                              |
| write:  | 0                          | 0              | 0                    | 0                            | 0                                      | 732264.267                             | 0                              |
| verify: | 15360                      | 0              | 0                    | 15360                        | 0                                      | 0.008                                  | 0                              |

non-medium error count: 154

no self-tests have been logged