



Model: HP EG0600FBDBU

S/N: PPGXGPBB

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HP EG0600FBDBU**

Serial: **PPGXGPBB**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/02/26 06:27:31**

End time: **2025/02/26 10:15:52**

Duration: **03:48:21**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **131 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HP EG0600FBDBU

S/N: PPGXGPBB

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: HP
product: EG0600FBDBU
revision: HPD5
compliance: SPC-3
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10020 rpm
form factor: 2.5 inches
logical unit id: 0x5000cca01233c620
serial number: PPGXGPBB
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 26 10:15:54 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

current drive temperature: 30 C
drive trip temperature: 65 C

accumulated power on time, hours:minutes 34690:43
manufactured in week 14 of year 2011
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 26
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 3948
elements in grown defect list: 399

error counter log:

	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
read:	0 53022588	0	5	0	312394.897	772
write:	0 593886	0	597594	0	186940.015	0
verify:	0 10731561	0	41081456406	0	281379.870	0

non-medium error count: 248

no self-tests have been logged