



Model: SEAGATE ST1200MM0129

S/N: WFK6W8GX0000C03659QD

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **SEAGATE ST1200MM0129**

Serial: **WFK6W8GX0000C03659QD**

Size(Apparent): **1200 GB, 1200243695616 bytes**

Bus: **SAS**

Size(Real): **1200 GB, 1200243695616 bytes**

Disk Erasure Details

Start time: **2025/02/26 06:29:14**

End time: **2025/02/26 12:19:14**

Duration: **05:50:00**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1200243695616, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **171 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST1200MM0129

S/N: WFK6W8GX0000C03659QD

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST1200MM0129
revision: C004
compliance: SPC-4
user capacity: 1,200,243,695,616 bytes [1.20 TB]
logical block size: 512 bytes
physical block size: 4096 bytes
lu is fully provisioned
rotation rate: 10500 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500c9f3d14f
serial number: WFK6W8GX0000C03659QD
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 26 12:19:15 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===
smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned <not available>
power on minutes since format <not available>
current drive temperature: 38 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 24923:10
manufactured in week 12 of year 2020
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 12
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 1181
elements in grown defect list: 0

vendor (seagate cache) information
blocks sent to initiator = 2348667608
blocks received from initiator = 393489120
blocks read from cache and sent to initiator = 76128
number of read and write commands whose size <= segment size = 10790
number of read and write commands whose size > segment size = 3

vendor (seagate/hitachi) factory information
number of hours powered up = 24923.17
number of minutes until next internal smart test = 23

error counter log:

	errors corrected by	total	correction	gigabytes	total
	ecc	rereads/	errors	processed	uncorrected
	fast delayed	rewrites	corrected	algorithm	errors
				invocations	[10^9 bytes]
read:	292395024	0	292395024	0	1200.331
write:	0	0	0	0	2400.516
verify:	533970	0	533970	0	2.187

non-medium error count: 0

[gltsd (global logging target save disable) set. enable save with '-s on']



Model: SEAGATE ST1200MM0129
S/N: WFK6W8GX0000C03659QD

Disk Erasure Report

Page 3 - Smart Data



no self-tests have been logged