



Model: SEAGATE ST1200MM0088

S/N: S401BH7Q

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST1200MM0088**

Serial: **S401BH7Q**

Size(Apparent): **1200 GB, 1200243695616 bytes**

Bus: **SAS**

Size(Real): **1200 GB, 1200243695616 bytes**

Disk Erasure Details

Start time: **2025/02/26 06:28:18**

End time: **2025/02/26 13:08:44**

Duration: **06:40:26**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1200243695616, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **149 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST1200MM0088

S/N: S401BH7Q

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

```
=== start of information section ===
vendor:                SEAGATE
product:               ST1200MM0088
revision:              TT31
compliance:            SPC-4
user capacity:         1,200,243,695,616 bytes [1.20 TB]
logical block size:    512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
lu is fully provisioned
rotation rate:         10000 rpm
form factor:           2.5 inches
logical unit id:       0x5000c50096933cdf
serial number:         S401BH7Q
device type:           disk
transport protocol:    SAS (SPL-3)
local time is:         Wed Feb 26 13:08:46 2025 GMT
smart support is:      Available - device has SMART capability.
smart support is:      Enabled
temperature warning:   Disabled or Not Supported
```

```
=== start of read smart data section ===
smart health status: OK
```

```
grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned = 0
power on minutes since format <not available>
current drive temperature:    32 C
drive trip temperature:       60 C
```

```
accumulated power on time, hours:minutes 50265:14
manufactured in week 08 of year 2016
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 28
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 23448
elements in grown defect list: 0
```

```
vendor (seagate cache) information
  blocks sent to initiator = 1400520190
  blocks received from initiator = 3415073825
  blocks read from cache and sent to initiator = 181786089
  number of read and write commands whose size <= segment size = 148547747
  number of read and write commands whose size > segment size = 9
```

```
vendor (seagate/hitachi) factory information
  number of hours powered up = 50265.23
  number of minutes until next internal smart test = 40
```

```
error counter log:
      errors corrected by      total  correction  gigabytes  total
      ecc      rereads/      errors  algorithm  processed  uncorrected
      fast | delayed  rewrites  corrected  invocations  [10^9 bytes]  errors
read:  2844874518      6      0  2844874524      6      471520.177      0
write:      0      0      36      36      36  35563.777      0
verify: 3932233091     54      0  3932233145     54  364493.333      0
```

```
non-medium error count:      4005
```

```
smart self-test log
```



Model: SEAGATE ST1200MM0088
S/N: S401BH7Q



Disk Erasure Report

Page 3 - Smart Data

num	test	status	segment	lifetime	lba_first_err	[sk	asc	asq]
	description		number	(hours)				
# 1	background short	completed	80	4	-	[-	-	-]
# 2	reserved(7)	completed	64	4	-	[-	-	-]

long (extended) self-test duration: 7630 seconds [127.2 minutes]