



Model: SEAGATE ST1200MM0088

S/N: S401BH8K

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST1200MM0088**

Serial: **S401BH8K**

Size(Apparent): **1200 GB, 1200243695616 bytes**

Bus: **SAS**

Size(Real): **1200 GB, 1200243695616 bytes**

Disk Erasure Details

Start time: **2025/02/26 06:30:24**

End time: **2025/02/26 14:20:52**

Duration: **07:50:28**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1200243695616, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **127 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST1200MM0088

S/N: S401BH8K

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST1200MM0088
revision: TT31
compliance: SPC-4
user capacity: 1,200,243,695,616 bytes [1.20 TB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c50096933c67
serial number: S401BH8K
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Feb 26 14:20:54 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned <not available>
power on minutes since format <not available>
current drive temperature: 33 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 50271:03
manufactured in week 08 of year 2016
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 28
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 7330
elements in grown defect list: 0

vendor (seagate cache) information
blocks sent to initiator = 3104035868
blocks received from initiator = 2458696423
blocks read from cache and sent to initiator = 1594912649
number of read and write commands whose size <= segment size = 454054948
number of read and write commands whose size > segment size = 9

vendor (seagate/hitachi) factory information
number of hours powered up = 50271.05
number of minutes until next internal smart test = 29

error counter log:		errors corrected by		total	correction	gigabytes	total
	ecc	fast delayed	rereads/ rewrites	errors corrected	algorithm invocations	processed [10^9 bytes]	uncorrected errors
read:	2387789227	0	0	2387789227	0	115068.093	0
write:	0	0	11	11	11	43834.849	0
verify:	3402165589	0	0	3402165589	0	364489.970	0

non-medium error count: 730

smart self-test log



Model: SEAGATE ST1200MM0088
S/N: S401BH8K



Disk Erasure Report

Page 3 - Smart Data

num	test	status	segment	lifetime	lba_first_err	[sk	asc	asq]
	description		number	(hours)				
# 1	background short	completed	80	4	-	[-	-	-]
# 2	reserved(7)	completed	64	4	-	[-	-	-]

long (extended) self-test duration: 7630 seconds [127.2 minutes]