



Model: SEAGATE ST1000NX0333

S/N: W471P8XZ0000E8349L70

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST1000NX0333**

Serial: **W471P8XZ0000E8349L70**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

## Disk Erasure Details

Start time: **2025/02/26 06:31:39**

End time: **2025/02/26 15:31:54**

Duration: **09:00:15**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **92 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST1000NX0333

S/N: W471P8XZ0000E8349L70

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST1000NX0333  
revision: E004  
compliance: SPC-4  
user capacity: 1,000,204,886,016 bytes [1.00 TB]  
logical block size: 512 bytes  
physical block size: 4096 bytes  
lu is fully provisioned  
rotation rate: 7200 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c500b8350783  
serial number: W471P8XZ0000E8349L70  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Wed Feb 26 15:31:59 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Enabled

=== start of read smart data section ===  
smart health status: OK

grown defects during certification <not available>  
total blocks reassigned during format <not available>  
total new blocks reassigned <not available>  
power on minutes since format <not available>  
current drive temperature: 31 C  
drive trip temperature: 60 C

accumulated power on time, hours:minutes 39296:53  
manufactured in week 17 of year 2018  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 11  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 1648  
elements in grown defect list: 0

vendor (seagate cache) information  
blocks sent to initiator = 1953851480  
blocks received from initiator = 3907050336  
blocks read from cache and sent to initiator = 194680  
number of read and write commands whose size <= segment size = 8082  
number of read and write commands whose size > segment size = 1199

vendor (seagate/hitachi) factory information  
number of hours powered up = 39296.88  
number of minutes until next internal smart test = 15

error counter log:		errors corrected by		total	correction	gigabytes	total
		ecc	rereads/	errors	algorithm	processed	uncorrected
		fast   delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	797879386	0	0	797879386	0	1000.372	0
write:	0	0	0	0	0	2000.414	0

non-medium error count: 0

[gltsd (global logging target save disable) set. enable save with '-s on']  
no self-tests have been logged



Model: SEAGATE ST1000NX0333  
S/N: W471P8XZ0000E8349L70

## Disk Erasure Report

Page 3 - Smart Data

