

Model: SEAGATE ST91000640SS  
S/N: 9XG2YEFN



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST91000640SS**

Serial: **9XG2YEFN**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

## Disk Erasure Details

Start time: **2025/02/26 09:38:36**

End time: **2025/02/26 19:13:39**

Duration: **09:35:03**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **86 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST91000640SS

S/N: 9XG2YEFN

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.22.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST91000640SS  
revision: AS06  
compliance: SPC-4  
user capacity: 1,000,204,886,016 bytes [1.00 TB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c500427cda03  
serial number: 9XG2YEFN  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Wed Feb 26 19:13:41 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 9743:27  
manufactured in week 39 of year 2012  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 32  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 7408  
elements in grown defect list: 33

vendor (seagate cache) information

blocks sent to initiator = 236340098  
blocks received from initiator = 3789481021  
blocks read from cache and sent to initiator = 1081169273  
number of read and write commands whose size <= segment size = 778902576  
number of read and write commands whose size > segment size = 2

vendor (seagate/hitachi) factory information

number of hours powered up = 9743.45  
number of minutes until next internal smart test = 59

error counter log:


	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 <sup>9</sup> bytes]	total uncorrected errors
read:	601004821	0	601004821	0	106200.053	0
write:	0	0	0	0	30836.577	0
verify:	1372572824	0	1372572824	0	411138.095	0

non-medium error count: 69

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err [sk asc asq]
# 1	background short	completed	32	5	- [- - -]
# 2	background long	completed	32	5	- [- - -]
# 3	background short	completed	32	1	- [- - -]

long (extended) self-test duration: 12198 seconds [203.3 minutes]



Model: SEAGATE ST91000640SS

S/N: 9XG2YEFN

# Disk Erasure Report

Page 3 - Smart Data

