



Model: SEAGATE ST4000NM0023

S/N: Z1Z9BLYR0000R604T7JA

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST4000NM0023**

Serial: **Z1Z9BLYR0000R604T7JA**

Size(Apparent): **4000 GB, 4000787030016 bytes**

Bus: **SAS**

Size(Real): **4000 GB, 4000787030016 bytes**

## Disk Erasure Details

Start time: **2025/02/26 06:26:22**

End time: **2025/02/27 08:17:40**

Duration: **25:51:18**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **4000787030016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **128 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST4000NM0023

S/N: Z1Z9BLYR0000R604T7JA

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST4000NM0023  
revision: 0004  
compliance: SPC-4  
user capacity: 4,000,787,030,016 bytes [4.00 TB]  
logical block size: 512 bytes  
lu is fully provisioned  
rotation rate: 7200 rpm  
form factor: 3.5 inches  
logical unit id: 0x5000c500840f1977  
serial number: Z1Z9BLYR0000R604T7JA  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Thu Feb 27 08:17:46 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

current drive temperature: 36 C  
drive trip temperature: 60 C

accumulated power on time, hours:minutes 61135:03  
manufactured in week 33 of year 2015  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 139  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 2685  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 76078753  
blocks received from initiator = 107701331  
blocks read from cache and sent to initiator = 901063318  
number of read and write commands whose size <= segment size = 2184791056  
number of read and write commands whose size > segment size = 122971

vendor (seagate/hitachi) factory information

number of hours powered up = 61135.05  
number of minutes until next internal smart test = 20

error counter log:

	errors corrected by ecc	total errors	correction algorithm	gigabytes processed	total uncorrected errors
	fast   delayed	rereads/ rewrites	corrected invocations	[10 <sup>9</sup> bytes]	
read:	938771149	0	0	730634.365	0
write:	0	0	0	593683.415	0

non-medium error count: 708

no self-tests have been logged