



Model: SEAGATE ST1200MM0007

S/N: S3L08RJW

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

## Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

## Disk Information

Make/Model: **SEAGATE ST1200MM0007**

Serial: **S3L08RJW**

Size(Apparent): **1200 GB, 1200243695616 bytes**

Bus: **SAS**

Size(Real): **1200 GB, 1200243695616 bytes**

## Disk Erasure Details

Start time: **2025/03/08 12:06:09**

End time: **2025/03/08 19:38:55**

Duration: **07:32:46**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **1200243695616, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **132 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST1200MM0007

S/N: S3L08RJW

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST1200MM0007  
revision: IS04  
compliance: SPC-4  
user capacity: 1,200,243,695,616 bytes [1.20 TB]  
logical block size: 512 bytes  
lu is fully provisioned  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c500721465a7  
serial number: S3L08RJW  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Sat Mar 8 19:38:57 2025 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 37 C  
drive trip temperature: 50 C

accumulated power on time, hours:minutes 43351:13  
manufactured in week 11 of year 2014  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 18  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 1396  
elements in grown defect list: 295

vendor (seagate cache) information

blocks sent to initiator = 434467391  
blocks received from initiator = 3869252188  
blocks read from cache and sent to initiator = 3158721175  
number of read and write commands whose size <= segment size = 197761500  
number of read and write commands whose size > segment size = 7270

vendor (seagate/hitachi) factory information

number of hours powered up = 43351.22  
number of minutes until next internal smart test = 49

error counter log:

	errors corrected by	total errors	correction algorithm	gigabytes processed	total uncorrected errors		
	ecc	errors	algorithm	processed	errors		
	fast   delayed	rereads/rewrites	corrected invocations	[10^9 bytes]			
read:	3698938564	172	0	3698938736	172	124066.625	0
write:	0	0	107	107	32493.328	0	0
verify:	1160663434	33	0	1160663467	62	242881.604	26

non-medium error count: 54430

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
# 1	background short	completed	48	3	-	[- - -]
# 2	background long	completed	48	3	-	[- - -]

long (extended) self-test duration: 8400 seconds [140.0 minutes]



Model: SEAGATE ST1200MM0007

S/N: S3L08RJW

# Disk Erasure Report

Page 3 - Smart Data

