



Model: SEAGATE ST91000640SS S/N: 9XG6YWQX

Disk Erasure Report





Organisation Performing The Disk Erasure

Business Name: GridJet

Business Address:

Contact Name: **GDW-LDS-6** Contact Phone:

Customer Details

Name: Gridjet

Address:

Contact Name: Contact Phone:

Disk Information

Make/Model: SEAGATE ST91000640SS Serial: 9XG6YWQX

Size(Apparent): 1000 GB, 1000204886016 bytes Bus: SAS

Size(Real): 1000 GB, 1000204886016 bytes

Disk Erasure Details

Start time: 2025/03/08 12:07:06 End time: 2025/03/08 22:29:10

Duration: 10:22:04 Status: **ERASED** See Warning!

Method: PRNG Stream PRNG algorithm: XORshiro256

Final Pass(Zeros/Ones/None): Zeros Verify Pass(Last/All/None): Verify Last

*Bytes Erased: 1000204886016, (100.00%) Rounds(completed/requested): 1/1

HPA/DCO: Unknown HPA/DCO Size: Unknown

Errors(pass/sync/verify): 0/0/0 Throughput: 80 MB/sec

Information: Warning HPA/DCO data unavailable, can not determine hidden sector status.

Technician/Operator ID Signature:

Name/ID: Auto Wipe

^{*} bytes erased: The amount of drive that's been erased at least once





Model: SEAGATE ST91000640SS S/N: 9XG6YWQX

Disk Erasure Report





```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
=== start of information section ===
vendor:
                       SEAGATE
product:
                       ST91000640SS
                       AS09
revision:
compliance:
                      SPC-4
user capacity:
                       1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm form factor: 2.5 inches
logical unit id: 0x5000c50058e1e09f
serial number: 9XG6YWQX
device type:
device type:
                      disk
transport protocol: SAS (SPL-3)
local time is: Sat Mar 8 22:29:25 2025 GMT smart support is: Available - device has SMART capability. smart support is: Enabled
temperature warning: Disabled or Not Supported
=== start of read smart data section ===
smart health status: OK
current drive temperature:
                                 32 C
drive trip temperature:
                                 68 C
accumulated power on time, hours:minutes 71453:05
manufactured in week 24 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 29
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 4426
elements in grown defect list: 0
vendor (seagate cache) information
  blocks sent to initiator = 3222375491
  blocks received from initiator = 2518288228
  blocks read from cache and sent to initiator = 380921211
  number of read and write commands whose size <= segment size = 290369025
  number of read and write commands whose size > segment size = 8
vendor (seagate/hitachi) factory information
  number of hours powered up = 71453.08
  number of minutes until next internal smart test = 59
error counter log:
                                          total correction gigabytes errors algorithm processed
           errors corrected by
                                                                                total
           ecc rereads/ errors algorithm processed fast | delayed rewrites corrected invocations [10^9 bytes]
                                                                                  uncorrected
                                                                                  errors
      509188224 0 0 509188224 0
read:
                                                                   97994.421
                                                     1
write:
               Ω
                         0
                                   1
                                                                 60832.054
                                                                                       Ω
verify: 3097307496
                          0
                                     0 3097307496
                                                                     339525.897
non-medium error count:
                              168
smart self-test log
                                                 segment lifetime lba_first_err [sk asc asq]
num test
                        status
                                                 number
     description
                                                          (hours)
# 1 background short completed
# 2 reserved(7) completed
                                                     32
                                                              3
                                                                                  - [- -
                                                                                               -]
# 3 background short completed
long (extended) self-test duration: 12198 seconds [203.3 minutes]
```





Model: SEAGATE ST91000640SS S/N: 9XG6YWQX

Disk Erasure Report

Page 3 - Smart Data

