



Model: SEAGATE ST91000640SS

S/N: 9XG6FPMD

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **SEAGATE ST91000640SS**

Serial: **9XG6FPMD**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/03/08 12:05:14**

End time: **2025/03/08 22:29:12**

Duration: **10:23:58**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **80 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST91000640SS

S/N: 9XG6FPMD

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST91000640SS
revision: AS09
compliance: SPC-4
user capacity: 1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500586c6ce7
serial number: 9XG6FPMD
device type: disk
transport protocol: SAS (SPL-3)
local time is: Sat Mar 8 22:29:14 2025 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 37 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 68586:01
manufactured in week 12 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 128
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 9040
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1203751939
blocks received from initiator = 1797772374
blocks read from cache and sent to initiator = 219351985
number of read and write commands whose size <= segment size = 87110239
number of read and write commands whose size > segment size = 6

vendor (seagate/hitachi) factory information

number of hours powered up = 68586.02
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by			total	correction		total
	ecc	rereads/		errors	algorithm	gigabytes	uncorrected
	fast delayed	rewrites	corrected	invocations	[10^9 bytes]	errors	
read:	3313084462	0	0	3313084462	0	9199.195	0
write:	0	0	0	0	0	5397.984	0
verify:	1492927278	0	0	1492927278	0	182500.221	0

non-medium error count: 684

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	32	15	- [- - -]	
# 2	reserved(7)	completed	32	14	- [- - -]	
# 3	background short	completed	32	12	- [- - -]	
# 4	background short	completed	32	2	- [- - -]	



Model: SEAGATE ST91000640SS
S/N: 9XG6FPMD

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 12198 seconds [203.3 minutes]