



Model: SEAGATE ST91000640SS

S/N: 9XG58DTX

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST91000640SS**

Serial: **9XG58DTX**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

## Disk Erasure Details

Start time: **2025/05/18 13:50:54**

End time: **2025/05/19 00:16:55**

Duration: **10:26:01**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **79 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST91000640SS

S/N: 9XG58DTX

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST91000640SS  
revision: AS09  
compliance: SPC-4  
user capacity: 1,000,204,886,016 bytes [1.00 TB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c500570a8663  
serial number: 9XG58DTX  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Mon May 19 00:17:11 2025 BST  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 55440:09  
manufactured in week 30 of year 2013  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 48  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 719  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 3265345214  
blocks received from initiator = 2703520517  
blocks read from cache and sent to initiator = 3006605346  
number of read and write commands whose size <= segment size = 90737541  
number of read and write commands whose size > segment size = 1

vendor (seagate/hitachi) factory information

number of hours powered up = 55440.15  
number of minutes until next internal smart test = 35

error counter log:

|         | errors corrected by<br>ecc | rereads/<br>rewrites | total<br>errors<br>corrected | correction<br>algorithm<br>invocations | gigabytes<br>processed<br>[10 <sup>9</sup> bytes] | total<br>uncorrected<br>errors |
|---------|----------------------------|----------------------|------------------------------|----------------------------------------|---------------------------------------------------|--------------------------------|
| read:   | 4097324174                 | 0                    | 4097324174                   | 0                                      | 20921.368                                         | 0                              |
| write:  | 0                          | 0                    | 0                            | 0                                      | 19023.114                                         | 0                              |
| verify: | 1309473098                 | 0                    | 1309473098                   | 0                                      | 80148.917                                         | 0                              |

non-medium error count: 8

smart self-test log

| num | test<br>description | status    | segment<br>number | lifetime<br>(hours) | lba_first_err | [sk asc asq] |
|-----|---------------------|-----------|-------------------|---------------------|---------------|--------------|
| # 1 | background short    | completed | 32                | 6                   | -             | [- - -]      |
| # 2 | background long     | completed | 32                | 5                   | -             | [- - -]      |
| # 3 | background short    | completed | 32                | 2                   | -             | [- - -]      |

long (extended) self-test duration: 12198 seconds [203.3 minutes]



Model: SEAGATE ST91000640SS

S/N: 9XG58DTX

## Disk Erasure Report

Page 3 - Smart Data

