



Model: ST1000DM003-9YN1

S/N: S1D1VSZ3

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **ST1000DM003-9YN1**

Serial: **S1D1VSZ3**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **ATA**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2025/06/03 12:18:46**

End time: **2025/06/03 17:40:21**

Duration: **05:21:35**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **155 MB/sec**

Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: ST1000DM003-9YN1

S/N: S1D1VSZ3

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

model family: Seagate Barracuda 7200.14 (AF)
device model: ST1000DM003-9YN162
serial number: S1D1VSZ3
lu wwn device id: 5 000c50 04b4da51b
firmware version: CC4H
user capacity: 1,000,204,886,016 bytes [1.00 TB]
sector sizes: 512 bytes logical, 4096 bytes physical
rotation rate: 7200 rpm
device is: In smartctl database [for details use: -P show]
ata version is: ATA8-ACS T13/1699-D revision 4
sata version is: SATA 3.0, 6.0 Gb/s (current: 6.0 Gb/s)
local time is: Tue Jun 3 17:40:23 2025 BST
smart support is: Available - device has SMART capability.
smart support is: Enabled

=== start of read smart data section ===

smart overall-health self-assessment test result: PASSED

general smart values:

offline data collection status: (0x00)Offline data collection activity
was never started.
auto offline data collection: Disabled.
self-test execution status: (0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: (575) seconds.
offline data collection
capabilities: (0x73) SMART execute Offline immediate.
auto offline data collection on/off support.
suspend offline collection upon new
command.
no offline surface scan supported.
self-test supported.
conveyance self-test supported.
selective self-test supported.
smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability: (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: (1) minutes.
extended self-test routine
recommended polling time: (106) minutes.
conveyance self-test routine
recommended polling time: (2) minutes.
sct capabilities: (0x3085)SCT Status supported.

smart attributes data structure revision number: 10

vendor specific smart attributes with thresholds:

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x000f	117	099	006	pre-fail	always	-	120388848
3	spin_up_time	0x0003	097	097	000	pre-fail	always	-	0
4	start_stop_count	0x0032	100	100	020	old_age	always	-	23
5	reallocated_sector_ct	0x0033	100	100	036	pre-fail	always	-	0
7	seek_error_rate	0x000f	087	060	030	pre-fail	always	-	508895040
9	power_on_hours	0x0032	075	017	000	old_age	always	-	22576
10	spin_retry_count	0x0013	100	100	097	pre-fail	always	-	0
12	power_cycle_count	0x0032	100	100	020	old_age	always	-	23



Model: ST1000DM003-9YN1

S/N: S1D1VSZ3



Disk Erasure Report

Page 3 - Smart Data

183	runtime_bad_block	0x0032	100	100	000	old_age	always	-	0
184	end-to-end_error	0x0032	100	100	099	old_age	always	-	0
187	reported_uncorrect	0x0032	100	100	000	old_age	always	-	0
188	command_timeout	0x0032	100	100	000	old_age	always	-	0 0 0
189	high_fly_writes	0x003a	099	099	000	old_age	always	-	1
190	airflow_temperature_cel	0x0022	073	057	045	old_age	always	-	27 (min/max 19/27)
191	g-sense_error_rate	0x0032	100	100	000	old_age	always	-	0
192	power-off_retract_count	0x0032	100	100	000	old_age	always	-	20
193	load_cycle_count	0x0032	001	001	000	old_age	always	-	314253
194	temperature_celsius	0x0022	027	043	000	old_age	always	-	27 (0 14 0 0 0)
197	current_pending_sector	0x0012	100	100	000	old_age	always	-	0
198	offline_uncorrectable	0x0010	100	100	000	old_age	offline	-	0
199	udma_crc_error_count	0x003e	200	200	000	old_age	always	-	0
240	head_flying_hours	0x0000	100	253	000	old_age	offline	-	100183h+16m+00.481s
241	total_lbas_written	0x0000	100	253	000	old_age	offline	-	186017806179103
242	total_lbas_read	0x0000	100	253	000	old_age	offline	-	202419835991655

smart error log version: 1
no errors logged

smart self-test log structure revision number 1

num	test_description	status	remaining	lifetime(hours)	lba_of_first_error
# 1	extended captive	completed without error	00%	7	-

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):
after scanning selected spans, do not read-scan remainder of disk.
if selective self-test is pending on power-up, resume after 0 minute delay.