

Model: SEAGATE ST33000650SS  
S/N: Z295SEKS



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-2**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST33000650SS**

Serial: **Z295SEKS**

Size(Apparent): **3000 GB, 3000592982016 bytes**

Bus: **SAS**

Size(Real): **3000 GB, 3000592982016 bytes**

## Disk Erasure Details

Start time: **2025/06/03 12:18:30**

End time: **2025/06/04 04:09:59**

Duration: **15:51:29**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **3000592982016, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/0**

Throughput: **105 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST33000650SS  
S/N: Z295SEKS



# Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST33000650SS  
revision: RE0D  
compliance: SPC-4  
user capacity: 3,000,592,982,016 bytes [3.00 TB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 3.5 inches  
logical unit id: 0x5000c50055e70e4f  
serial number: Z295SEKS  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Wed Jun 4 04:10:00 2025 BST  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Enabled

=== start of read smart data section ===

smart health status: FAILURE PREDICTION THRESHOLD EXCEEDED: ascq=0x5 [asc=5d, ascq=5]

current drive temperature: 32 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 18945:58  
manufactured in week 52 of year 2012  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 129  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 253  
elements in grown defect list: 7688

vendor (seagate cache) information

blocks sent to initiator = 890530752  
blocks received from initiator = 2712935450  
blocks read from cache and sent to initiator = 856179328  
number of read and write commands whose size <= segment size = 2772251109  
number of read and write commands whose size > segment size = 638

vendor (seagate/hitachi) factory information

number of hours powered up = 18945.97  
number of minutes until next internal smart test = 59

error counter log:


	errors corrected by			total	correction	gigabytes	total
	ecc	rereads/		errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	2893290936	11	0	2893290947	13	867573.091	2
write:	0	0	0	0	0	107920.832	0
verify:	179081189	16957	0	179098146	16958	319414.821	16

non-medium error count: 2825

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	32	65535	- [- - -]	
# 2	background short	completed	32	65535	- [- - -]	

long (extended) self-test duration: 27600 seconds [460.0 minutes]



Model: SEAGATE ST33000650SS  
S/N: Z295SEKS

## Disk Erasure Report

Page 3 - Smart Data

