



Model: TOSHIBA AL13SXB600N

S/N: 85D0A2UEF91A

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **TOSHIBA AL13SXB600N**

Serial: **85D0A2UEF91A**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2025/06/04 11:04:34**

End time: **2025/06/04 14:21:32**

Duration: **03:16:58**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **152 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA AL13SXB600N

S/N: 85D0A2UEF91A

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA
product: AL13SXB600N
revision: DF05
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 2.5 inches
logical unit id: 0x500003967818fa49
serial number: 85D0A2UEF91A
device type: disk
transport protocol: SAS (SPL-3)
local time is: Wed Jun 4 14:21:34 2025 BST
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 38 C
drive trip temperature: 65 C

accumulated power on time, hours:minutes 72590:22
manufactured in week 33 of year 2015
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 10
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 7621
elements in grown defect list: 0

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc			errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10 ⁹ bytes]	errors
read:	0	246	246	246	1805	2793946.911	0
write:	0	605	605	605	962	142875.967	0
verify:	0	0	0	0	0	258106.390	0

non-medium error count: 4

smart self-test log

num	test	status		segment	lifetime	lba_first_err	[sk asc asq]
	description			number	(hours)		
# 1	background short	completed		64	12020	- [- - -]	

long (extended) self-test duration: 3163 seconds [52.7 minutes]