



Model: SEAGATE ST9500620SS  
S/N: 9XF3DM9S



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST9500620SS**

Serial: **9XF3DM9S**

Size(Apparent): **500 GB, 500107862016 bytes**

Bus: **SAS**

Size(Real): **500 GB, 500107862016 bytes**

## Disk Erasure Details

Start time: **2025/06/04 11:08:00**

End time: **2025/06/04 16:21:08**

Duration: **05:13:08**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **500107862016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **79 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9500620SS  
S/N: 9XF3DM9S



# Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST9500620SS  
revision: AS0D  
compliance: SPC-4  
user capacity: 500,107,862,016 bytes [500 GB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c50062ef99e7  
serial number: 9XF3DM9S  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Wed Jun 4 16:21:10 2025 BST  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 33 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 70360:28  
manufactured in week 48 of year 2014  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 120  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 3064  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 3960126913  
blocks received from initiator = 360344763  
blocks read from cache and sent to initiator = 2001564533  
number of read and write commands whose size <= segment size = 568718757  
number of read and write commands whose size > segment size = 33

vendor (seagate/hitachi) factory information

number of hours powered up = 70360.47  
number of minutes until next internal smart test = 43

error counter log:


	errors corrected by ecc	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10 <sup>9</sup> bytes]	total uncorrected errors
read:	2304923400	0	2304923400	0	74010.272	0
write:	0	0	0	0	13566.215	0
verify:	2285826304	0	2285826304	0	206356.964	0

non-medium error count: 45

smart self-test log

num	test description	status	segment number	lifetime (hours)	lba_first_err [sk asc asq]
# 1	background short	completed	32	3	- [- - -]
# 2	reserved(7)	completed	32	3	- [- - -]
# 3	background short	completed	32	1	- [- - -]

long (extended) self-test duration: 6099 seconds [101.7 minutes]



Model: SEAGATE ST9500620SS  
S/N: 9XF3DM9S

# Disk Erasure Report

Page 3 - Smart Data

