



Model: TOSHIBA AL13SEB600

S/N: Z440A0ORFRD3

# Disk Erasure Report

Page 1 - Erasure Status



## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **TOSHIBA AL13SEB600**

Serial: **Z440A0ORFRD3**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

## Disk Erasure Details

Start time: **2026/01/20 14:13:43**

End time: **2026/01/20 17:37:56**

Duration: **03:24:13**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **146 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA AL13SEB600

S/N: Z440A00RFRD3

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.22.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA  
product: AL13SEB600  
revision: DE11  
compliance: SPC-4  
user capacity: 600,127,266,816 bytes [600 GB]  
logical block size: 512 bytes  
rotation rate: 10000 rpm  
form factor: 2.5 inches  
logical unit id: 0x50000395f8039d20  
serial number: Z440A00RFRD3  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Tue Jan 20 17:37:57 2026 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 30 C  
drive trip temperature: 65 C

accumulated power on time, hours:minutes 84817:12  
manufactured in week 49 of year 2014  
specified cycle count over device lifetime: 50000  
accumulated start-stop cycles: 34  
specified load-unload count over device lifetime: 200000  
accumulated load-unload cycles: 11744  
elements in grown defect list: 0

error counter log:

|         | errors corrected by ecc | total errors corrected | correction algorithm | gigabytes processed [10 <sup>9</sup> bytes] | total uncorrected errors |
|---------|-------------------------|------------------------|----------------------|---------------------------------------------|--------------------------|
| read:   | fast   delayed   439    | 439                    | 1909                 | 3738747.835                                 | 0                        |
| write:  | 0   378                 | 379                    | 918                  | 297178.488                                  | 1                        |
| verify: | 0   93                  | 93                     | 95                   | 273188.957                                  | 0                        |

non-medium error count: 28

smart self-test log

| num | test description | status    | segment number | lifetime (hours) | lba_first_err | [sk asc asq] |
|-----|------------------|-----------|----------------|------------------|---------------|--------------|
| # 1 | background short | completed | 64             | 4                | -             | [- - -]      |
| # 2 | background long  | completed | 64             | 3                | -             | [- - -]      |
| # 3 | background short | completed | 64             | 2                | -             | [- - -]      |

long (extended) self-test duration: 3964 seconds [66.1 minutes]