



Model: HITACHI HUC106060CSS600

S/N: PZHNXHKD



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HITACHI HUC106060CSS600**

Serial: **PZHNXHKD**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/20 14:14:02**

End time: **2026/01/20 17:52:31**

Duration: **03:38:29**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **137 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HITACHI HUC106060CSS600
S/N: PZHNXHKD



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor: HITACHI
product: HUC106060CSS600
revision: A440
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000cca03c5e67ac
serial number: PZHNXHKD
device type: disk
transport protocol: SAS (SPL-3)
local time is: Tue Jan 20 17:52:34 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ====
smart health status: OK
```

```
current drive temperature: 31 C
drive trip temperature: 85 C
```

```
accumulated power on time, hours:minutes 5585:12
manufactured in week 50 of year 2012
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 60
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 2768
elements in grown defect list: 0
```

```
vendor (seagate cache) information
blocks sent to initiator = 71380379281391616
```

```
error counter log:
      errors corrected by      total      correction      gigabytes      total
      ecc          rereads/    errors    algorithm    processed      uncorrected
      fast | delayed    rewrites  corrected  invocations [10^9 bytes]  errors
read:  3593845834    3210264      0  3597056098  27373145  162531.351      2
write:      0    497415      0  497415    499058  139981.398      0
verify: 9420042098    29834      0  9420071932    86404  212424.888      0
```

```
non-medium error count: 7
```

```
smart self-test log
num  test      status      segment      lifetime      lba_first_err [sk asc asq]
     description      number      (hours)
# 1  background short completed      32          3          - [-] - [-]
# 2  background long  completed      32          3          - [-] - [-]
# 3  background short completed      32          2          - [-] - [-]
```

```
long (extended) self-test duration: 4889 seconds [81.5 minutes]
```