



Model: HGST HUC101860CSS200

S/N: 03HVLNGB



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HGST HUC101860CSS200**

Serial: **03HVLNGB**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/20 14:52:53**

End time: **2026/01/20 17:54:39**

Duration: **03:01:46**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **165 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HGST HUC101860CSS200

S/N: 03HVLNGB



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor:           HGST
product:          HUC101860CSS200
revision:         FU39
compliance:       SPC-4
user capacity:    600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
lu is fully provisioned
rotation rate:    10000 rpm
form factor:      2.5 inches
logical unit id: 0x5000cca02f68bcc
serial number:    03HVLNGB
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Tue Jan 20 17:54:43 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ===
smart health status: OK
```

```
current drive temperature:    32 C
drive trip temperature:       50 C

accumulated power on time, hours:minutes 26960:26
manufactured in week 04 of year 2019
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 16
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 1139
elements in grown defect list: 0
```

```
vendor (seagate cache) information
blocks sent to initiator = 16309926880083968
```

```
error counter log:
      errors corrected by          total  correction      gigabytes      total
      ecc          rereads/  errors    algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:      0        32        0       207    6624924    50503.124      0
write:     0        0        0       0      258558    51836.192      0
verify:    0       10        0       62     82420    78017.105      0
```

```
non-medium error count:      0
```

```
smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number    (hours)
# 1  reserved(7)  completed        64        3          - [- - -]
# 2  background short completed        96        1          - [- - -]
```

```
long (extended) self-test duration: 4580 seconds [76.3 minutes]
```