



Model: WD WD6001BKHG

S/N: WXN1E32NTTSZ



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WD WD6001BKHG**

Serial: **WXN1E32NTTSZ**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/20 14:14:12**

End time: **2026/01/20 18:20:27**

Duration: **04:06:15**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **121 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD6001BKHG

S/N: WZN1E32NTTSZ



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor: WD
product: WD6001BKHG
revision: D1S6
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000c0f02bb48e8
serial number: WZN1E32NTTSZ
device type: disk
transport protocol: SAS (SPL-3)
local time is: Tue Jan 20 18:20:31 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ====
smart health status: OK
```

```
current drive temperature: 29 C
drive trip temperature: 64 C
```

```
accumulated power on time, hours:minutes 64301:42
manufactured in week 05 of year 2013
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 30
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 36108
elements in grown defect list: 0
```

```
error counter log:
      errors corrected by          total  correction  gigabytes  total
      ecc          rereads/  errors  algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:  371757023   353818   1302838  372110841   353820   92324.989          2
write: 277694051   59352    16701  277753403   59352   128262.151          0
verify: 1117978   314491   1295519  1432469   314491   5874.728          0
```

```
non-medium error count: 569
```

```
smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number    (hours)
# 1  background short completed      32        3          - [- - -]
# 2  background long  aborted (by user command) 32        3          - [- - -]
# 3  background short aborted (by user command) 32        1          - [- - -]
```

```
long (extended) self-test duration: 4144 seconds [69.1 minutes]
```