



Model: **TOSHIBA AL13SXB600N**

S/N: **85D0A2UEF91A**



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **TOSHIBA AL13SXB600N**

Serial: **85D0A2UEF91A**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/20 15:49:10**

End time: **2026/01/20 18:41:58**

Duration: **02:52:48**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **173 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA AL13SXB600N

S/N: 85D0A2UEF91A



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor: TOSHIBA
product: AL13SXB600N
revision: DF05
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 2.5 inches
logical unit id: 0x500003967818fa49
serial number: 85D0A2UEF91A
device type: disk
transport protocol: SAS (SPL-3)
local time is: Tue Jan 20 18:42:10 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ===
smart health status: OK
```

```
current drive temperature: 38 C
drive trip temperature: 65 C
```

```
accumulated power on time, hours:minutes 78111:32
manufactured in week 33 of year 2015
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 11
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 7852
elements in grown defect list: 0
```

```
error counter log:
      errors corrected by          total  correction      gigabytes      total
      ecc          rereads/  errors  algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:      0      247      247      247      1813  2933664.346      0
write:     0      607      607      607      966   144165.612      0
verify:    0       0       0       0       0   258106.390      0
```

```
non-medium error count: 4
```

```
smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number    (hours)
# 1  background short  completed        64    12020          - [- - -]
```

```
long (extended) self-test duration: 3163 seconds [52.7 minutes]
```