



Model: SEAGATE ST9500620SS  
S/N: 9XF3D255



# Disk Erasure Report

Page 1 - Erasure Status

## Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

## Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

## Disk Information

Make/Model: **SEAGATE ST9500620SS**

Serial: **9XF3D255**

Size(Apparent): **500 GB, 500107862016 bytes**

Bus: **SAS**

Size(Real): **500 GB, 500107862016 bytes**

## Disk Erasure Details

Start time: **2026/01/20 15:49:10**

End time: **2026/01/20 20:24:58**

Duration: **04:35:48**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **500107862016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **90 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

\* bytes erased: The amount of drive that's been erased at least once

## Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9500620SS

S/N: 9XF3D255

# Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86\_64-linux-5.14.0-503.23.1.el9\_5.x86\_64] (local build)  
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE  
product: ST9500620SS  
revision: AS0D  
compliance: SPC-4  
user capacity: 500,107,862,016 bytes [500 GB]  
logical block size: 512 bytes  
rotation rate: 7200 rpm  
form factor: 2.5 inches  
logical unit id: 0x5000c50062d511a7  
serial number: 9XF3D255  
device type: disk  
transport protocol: SAS (SPL-3)  
local time is: Tue Jan 20 20:25:07 2026 GMT  
smart support is: Available - device has SMART capability.  
smart support is: Enabled  
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C  
drive trip temperature: 68 C

accumulated power on time, hours:minutes 70319:34  
manufactured in week 46 of year 2014  
specified cycle count over device lifetime: 10000  
accumulated start-stop cycles: 131  
specified load-unload count over device lifetime: 300000  
accumulated load-unload cycles: 12309  
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 2235850205  
blocks received from initiator = 991546887  
blocks read from cache and sent to initiator = 1705910436  
number of read and write commands whose size <= segment size = 875846000  
number of read and write commands whose size > segment size = 18

vendor (seagate/hitachi) factory information

number of hours powered up = 70319.57  
number of minutes until next internal smart test = 54

error counter log:

|         | errors corrected by<br>ecc | rereads/<br>rewrites | total<br>errors<br>corrected | correction<br>algorithm<br>invocations | gigabytes<br>processed<br>[10 <sup>9</sup> bytes] | total<br>uncorrected<br>errors |
|---------|----------------------------|----------------------|------------------------------|----------------------------------------|---------------------------------------------------|--------------------------------|
| read:   | 1877603474                 | 0                    | 0                            | 1877603474                             | 0                                                 | 820942.114                     |
| write:  | 0                          | 0                    | 0                            | 0                                      | 31451.687                                         | 0                              |
| verify: | 944515583                  | 1                    | 0                            | 944515584                              | 1                                                 | 203693.348                     |

non-medium error count: 54

smart self-test log

| num | test             | status    | segment<br>number | lifetime<br>(hours) | lba_first_err | [sk asc asq] |
|-----|------------------|-----------|-------------------|---------------------|---------------|--------------|
| # 1 | background short | completed | 32                | 4                   | -             | [- - -]      |
| # 2 | reserved(7)      | completed | 32                | 4                   | -             | [- - -]      |
| # 3 | background short | completed | 32                | 2                   | -             | [- - -]      |

long (extended) self-test duration: 6099 seconds [101.7 minutes]



Model: SEAGATE ST9500620SS  
S/N: 9XF3D255

# Disk Erasure Report

Page 3 - Smart Data

