

Model: **SEAGATE ST600MM0006**

S/N: **S0M4V7TK**



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST600MM0006**

Serial: **S0M4V7TK**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/21 11:42:06**

End time: **2026/01/21 14:58:13**

Duration: **03:16:07**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **153 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST600MM0006
S/N: S0M4V7TK



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor:           SEAGATE
product:          ST600MM0006
revision:         LS0A
compliance:       SPC-4
user capacity:    600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate:    10000 rpm
form factor:      2.5 inches
logical unit id: 0x5000c500880cfc8f
serial number:    S0M4V7TK
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Wed Jan 21 14:58:15 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

==== start of read smart data section ====
smart health status: DATA CHANNEL IMPENDING FAILURE GENERAL HARD DRIVE FAILURE [asc=5d, ascq=30]

current drive temperature:    32 C
drive trip temperature:       50 C

accumulated power on time, hours:minutes 14855:57
manufactured in week 06 of year 2015
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 141
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 4062
elements in grown defect list: 13


vendor (seagate cache) information
blocks sent to initiator = 551577233
blocks received from initiator = 3375760253
blocks read from cache and sent to initiator = 716332145
number of read and write commands whose size <= segment size = 986366255
number of read and write commands whose size > segment size = 274025

vendor (seagate/hitachi) factory information
number of hours powered up = 14855.95
number of minutes until next internal smart test = 52

error counter log:
      errors corrected by          total  correction  gigabytes  total
      ecc      rereads/  errors  algorithm  processed  [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:  914045486      23      0  914045509      42  2268232.450      19
write:      0      0      30      30      30  335071.110      0
verify: 2121904079     103      0  2121904182     1177  328087.106     1062

non-medium error count: 110

smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number  (hours)
# 1  background short completed      64        3          - [- - -]
# 2  reserved(7)  completed      48        3          - [- - -]
# 3  background short completed      64        1          - [- - -]
```



Model: SEAGATE ST600MM0006

S/N: S0M4V7TK

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 3777 seconds [63.0 minutes]