



Model: SEAGATE ST4000NM0023

S/N: Z1ZAMJ350000R631N3J5



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST4000NM0023**

Serial: **Z1ZAMJ350000R631N3J5**

Size(Apparent): **4000 GB, 4000787030016 bytes**

Bus: **SAS**

Size(Real): **4000 GB, 4000787030016 bytes**

Disk Erasure Details

Start time: **2026/01/20 14:52:07**

End time: **2026/01/21 15:20:35**

Duration: **24:28:28**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **4000787030016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **136 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST4000NM0023

S/N: Z1ZAMJ350000R631N3J5



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor:           SEAGATE
product:          ST4000NM0023
revision:         0004
compliance:       SPC-4
user capacity:    4,000,787,030,016 bytes [4.00 TB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate:    7200 rpm
form factor:      3.5 inches
logical unit id: 0x5000c500851dce9b
serial number:    Z1ZAMJ350000R631N3J5
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Wed Jan 21 15:20:36 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled
```

```
==== start of read smart data section ===
smart health status: OK
```

```
current drive temperature:    37 C
drive trip temperature:       60 C
```

```
accumulated power on time, hours:minutes 64067:22
manufactured in week 08 of year 2016
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 166
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 2817
elements in grown defect list: 2
```

```
vendor (seagate cache) information
blocks sent to initiator = 3519224835
blocks received from initiator = 2743180119
blocks read from cache and sent to initiator = 5544
number of read and write commands whose size <= segment size = 217795
number of read and write commands whose size > segment size = 0
```

```
vendor (seagate/hitachi) factory information
number of hours powered up = 64067.37
number of minutes until next internal smart test = 30
```

```
error counter log:
      errors corrected by          total  correction      gigabytes      total
      ecc      rereads/  errors  algorithm  processed  [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:  704510690      0        0  704510690          0      2514.808          0
write:     0        0        0          0          0      8010.128          0
```

```
non-medium error count:      14
```

```
[gltsd (global logging target save disable) set. enable save with '-s on']
no self-tests have been logged
```