



Model: INTEL SSDSC2BA40
S/N: BTTV437400SX400HGN



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **INTEL SSDSC2BA40**

Serial: **BTTV437400SX400HGN**

Size(Apparent): **400 GB, 400088457216 bytes**

Bus: **ATA-SSD**

Size(Real): **400 GB, 400088457216 bytes**

Disk Erasure Details

Start time: **2026/01/21 12:08:11**

End time: **2026/01/21 15:24:00**

Duration: **03:15:49**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **400088457216, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **102 MB/sec**

Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: INTEL SSDSC2BA40
S/N: BTTV437400SX400HGN



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

model family: Intel 730 and DC S35x0/3610/3700 Series SSDs
device model: INTEL SSDSC2BA400G3T
serial number: BTTV437400SX400HGN
lu wwn device id: 5 5cd2e4 04b6dfdbc
add. product id: DELL(tm)
firmware version: 5DV1DL08
user capacity: 400,088,457,216 bytes [400 GB]
sector sizes: 512 bytes logical, 4096 bytes physical
rotation rate: Solid State Device
form factor: 2.5 inches
trim command: Available, deterministic, zeroed
device is: In smartctl database [for details use: -P show]
ata version is: ACS-2 T13/2015-D revision 3
sata version is: SATA 2.6, 6.0 Gb/s (current: 3.0 Gb/s)
local time is: Wed Jan 21 15:24:02 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled

=== start of read smart data section ===

smart overall-health self-assessment test result: PASSED

general smart values:

offline data collection status: (0x02)Offline data collection activity
was completed without error.
auto offline data collection: Disabled.
self-test execution status: (0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: (2) seconds.
offline data collection
capabilities: (0x79) SMART execute Offline immediate.
no auto offline data collection support.
suspend offline collection upon new
command.
offline surface scan supported.
self-test supported.
conveyance self-test supported.
selective self-test supported.
smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability: (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: (1) minutes.
extended self-test routine
recommended polling time: (60) minutes.
conveyance self-test routine
recommended polling time: (60) minutes.
sct capabilities: (0x003d)SCT Status supported.
sct error recovery control supported.
sct feature control supported.
sct data table supported.

smart attributes data structure revision number: 1

vendor specific smart attributes with thresholds:

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x000f	130	130	039	pre-fail	always	-	781424161
5	reallocated_sector_ct	0x0033	100	100	001	pre-fail	always	-	0



Model: INTEL SSDSC2BA40

S/N: BTTV437400SX400HGN



Disk Erasure Report

Page 3 - Smart Data

9	power_on_hours	0x0032	100	100	000	old_age	always	-	93442
12	power_cycle_count	0x0032	100	100	000	old_age	always	-	30
13	read_soft_error_rate	0x0032	128	100	000	old_age	always	-	781424161
179	used_rsvd_blk_cnt_tot	0x0033	100	100	010	pre-fail	always	-	0
180	unused_rsvd_blk_cnt_tot	0x0032	100	100	000	old_age	always	-	66530
181	program_fail_cnt_total	0x003a	100	100	000	old_age	always	-	0
182	erase_fail_count_total	0x003a	100	100	000	old_age	always	-	0
184	end-to-end_error	0x0032	100	100	000	old_age	always	-	0
194	temperature_internal	0x0022	100	100	000	old_age	always	-	35
195	hardware_ecc_recovered	0x0032	100	100	000	old_age	always	-	0
198	offline_uncorrectable	0x0010	100	100	000	old_age	offline	-	0
199	crc_error_count	0x003e	100	100	000	old_age	always	-	0
201	unknown_ssd_attribute	0x0033	100	100	010	pre-fail	always	-	2400899564143
226	workld_media_wear_indic	0x0032	100	100	000	old_age	always	-	583
227	workld_host_reads_perc	0x0032	100	100	000	old_age	always	-	81
228	workload_minutes	0x0032	100	100	000	old_age	always	-	5606343
233	media_wearout_indicator	0x0032	100	100	000	old_age	always	-	746188
245	unknown_attribute	0x0032	100	100	000	old_age	always	-	0

smart error log version: 1
no errors logged

smart self-test log structure revision number 1

num	test_description	status	remaining	lifetime(hours)	lba_of_first_error
# 1	short offline	completed without error	00%	3	-
# 2	extended offline	completed without error	00%	2	-
# 3	short offline	completed without error	00%	2	-

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.
if selective self-test is pending on power-up, resume after 0 minute delay.