



Model: **SEAGATE ST91000640SS**

S/N: **9XG54BFC**



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST91000640SS**

Serial: **9XG54BFC**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2026/01/21 12:04:24**

End time: **2026/01/21 21:42:57**

Duration: **09:38:33**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **86 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST91000640SS

S/N: 9XG54BFC



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor:           SEAGATE
product:          ST91000640SS
revision:         AS08
compliance:       SPC-4
user capacity:    1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
rotation rate:    7200 rpm
form factor:      2.5 inches
logical unit id:  0x5000c50056f4cf6f
serial number:    9XG54BFC
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Wed Jan 21 21:42:59 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ===
smart health status: OK
```

```
current drive temperature:    31 C
drive trip temperature:       68 C
```

```
accumulated power on time, hours:minutes 25531:14
manufactured in week 29 of year 2013
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 30
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 12970
elements in grown defect list: 1127
```

```
vendor (seagate cache) information
blocks sent to initiator = 3994030440
blocks received from initiator = 1223688931
blocks read from cache and sent to initiator = 2139075773
number of read and write commands whose size <= segment size = 248137809
number of read and write commands whose size > segment size = 0
```

```
vendor (seagate/hitachi) factory information
number of hours powered up = 25531.23
number of minutes until next internal smart test = 39
```

```
error counter log:
      errors corrected by          total  correction    gigabytes    total
      ecc      rereads/  errors   algorithm  processed  uncorrected
      fast | delayed  rewrites  corrected  invocations  [10^9 bytes]  errors
read:  914179703      6        0  914179709      6    120206.222        0
write:     0        0        0        0        0    18546.751        0
verify: 1594445376      7        0  1594445383      7    126265.310        0
```

```
non-medium error count: 1066
```

```
no self-tests have been logged
```