



Model: HGST HTS721010A9

S/N: JR10044M032DTN

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-0**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HGST HTS721010A9**

Serial: **JR10044M032DTN**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **ATA**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2026/01/21 15:55:14**

End time: **2026/01/21 23:49:24**

Duration: **07:54:10**

Status: **ERASED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **No hidden sectors**

HPA/DCO Size: **No hidden sectors**

Errors(pass/sync/verify): **0/0/0**

Throughput: **105 MB/sec**

Information:

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HGST HTS721010A9

S/N: JR10044M032DTN

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

model family: HGST Travelstar 7K1000
device model: HGST HTS721010A9E630
serial number: JR10044M032DTN
lu wwn device id: 5 000cca 8a8c1662b
firmware version: JB00A3J0
user capacity: 1,000,204,886,016 bytes [1.00 TB]
sector sizes: 512 bytes logical, 4096 bytes physical
rotation rate: 7200 rpm
form factor: 2.5 inches
device is: In smartctl database [for details use: -P show]
ata version is: ATA8-ACS T13/1699-D revision 6
sata version is: SATA 3.0, 6.0 Gb/s (current: 6.0 Gb/s)
local time is: Wed Jan 21 23:49:35 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled

=== start of read smart data section ===

smart overall-health self-assessment test result: PASSED

general smart values:

offline data collection status: (0x00)Offline data collection activity
was never started.
auto offline data collection: Disabled.
self-test execution status: (0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: (45) seconds.
offline data collection
capabilities: (0x5b) SMART execute Offline immediate.
auto offline data collection on/off support.
suspend offline collection upon new
command.
offline surface scan supported.
self-test supported.
no conveyance self-test supported.
selective self-test supported.
smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability: (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: (2) minutes.
extended self-test routine
recommended polling time: (162) minutes.
sct capabilities: (0x003d)SCT Status supported.
sct error recovery control supported.
sct feature control supported.
sct data table supported.

smart attributes data structure revision number: 16

vendor specific smart attributes with thresholds:

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x000b	100	100	062	pre-fail	always	-	0
2	throughput_performance	0x0005	100	100	040	pre-fail	offline	-	0
3	spin_up_time	0x0007	100	100	033	pre-fail	always	-	2
4	start_stop_count	0x0012	100	100	000	old_age	always	-	4
5	reallocated_sector_ct	0x0033	093	093	005	pre-fail	always	-	0
7	seek_error_rate	0x000b	100	100	067	pre-fail	always	-	0



Model: HGST HTS721010A9

S/N: JR10044M032DTN

Disk Erasure Report

Page 3 - Smart Data



8	seek_time_performance	0x0005	100	100	040	pre-fail	offline	-	0
9	power_on_hours	0x0012	001	001	000	old_age	always	-	75353
10	spin_retry_count	0x0013	100	100	060	pre-fail	always	-	0
12	power_cycle_count	0x0032	100	100	000	old_age	always	-	4
191	g-sense_error_rate	0x000a	100	100	000	old_age	always	-	0
192	power-off_retract_count	0x0032	100	100	000	old_age	always	-	2
193	load_cycle_count	0x0012	001	001	000	old_age	always	-	3076933
194	temperature_celsius	0x0002	240	240	000	old_age	always	-	25 (min/max 15/46)
196	reallocated_event_count	0x0032	019	019	000	old_age	always	-	2055
197	current_pending_sector	0x0022	100	100	000	old_age	always	-	0
198	offline_uncorrectable	0x0008	100	100	000	old_age	offline	-	0
199	udma_crc_error_count	0x000a	200	200	000	old_age	always	-	0
223	load_retry_count	0x000a	100	100	000	old_age	always	-	0

smart error log version: 1

ata error count: 11745 (device log contains only the most recent five errors)

cr = command register [hex]

fr = features register [hex]

sc = sector count register [hex]

sn = sector number register [hex]

cl = cylinder low register [hex]

ch = cylinder high register [hex]

dh = device/head register [hex]

dc = device command register [hex]

er = error register [hex]

st = status register [hex]

powered_up_time is measured from power on, and printed as

ddd+hh:mm:ss.sss where DD=days, hh=hours, mm=minutes,

ss=sec, and sss=millisec. it "wraps" after 49.710 days.

error 11745 occurred at disk power-on lifetime: 34061 hours (1419 days + 5 hours)
when the command that caused the error occurred, the device was active or idle.

after command completion occurred, registers were:

er st sc sn cl ch dh

-- -- -- -- --

40 51 00 5f fd b3 01 error: UNC at LBA = 0x01b3fd5f = 28573023

commands leading to the command that caused the error were:

cr	fr	sc	sn	cl	ch	dh	dc	powered_up_time	command/feature_name
----	----	----	----	----	----	----	----	-----------------	----------------------

-- -- -- -- --

42	00	00	5f	fd	b3	40	00	15:31:07.344	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

42	00	01	5e	fd	b3	40	00	15:31:07.156	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

61	01	00	5e	fd	b3	40	00	15:31:07.156	WRITE FPDMA QUEUED
----	----	----	----	----	----	----	----	--------------	--------------------

61	20	08	58	44	d2	40	00	15:31:07.147	WRITE FPDMA QUEUED
----	----	----	----	----	----	----	----	--------------	--------------------

61	20	40	d8	ae	c6	40	00	15:31:07.147	WRITE FPDMA QUEUED
----	----	----	----	----	----	----	----	--------------	--------------------

error 11744 occurred at disk power-on lifetime: 34061 hours (1419 days + 5 hours)
when the command that caused the error occurred, the device was active or idle.

after command completion occurred, registers were:

er st sc sn cl ch dh

-- -- -- -- --

40 51 00 5e fd b3 01 error: UNC at LBA = 0x01b3fd5e = 28573022

commands leading to the command that caused the error were:

cr	fr	sc	sn	cl	ch	dh	dc	powered_up_time	command/feature_name
----	----	----	----	----	----	----	----	-----------------	----------------------

-- -- -- -- --

42	00	00	5e	fd	b3	40	00	15:31:07.003	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

42	00	01	5d	fd	b3	40	00	15:31:06.825	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

61	01	00	5d	fd	b3	40	00	15:31:06.825	WRITE FPDMA QUEUED
----	----	----	----	----	----	----	----	--------------	--------------------

61	10	00	50	f9	a6	40	00	15:31:06.788	WRITE FPDMA QUEUED
----	----	----	----	----	----	----	----	--------------	--------------------

42	00	00	5d	fd	b3	40	00	15:31:06.644	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------



Model: HGST HTS721010A9

S/N: JR10044M032DTN

Disk Erasure Report

Page 4 - Smart Data



error 11743 occurred at disk power-on lifetime: 34061 hours (1419 days + 5 hours)
when the command that caused the error occurred, the device was active or idle.

after command completion occurred, registers were:

er st sc sn cl ch dh

-- -- -- -- --

40 51 00 5d fd b3 01 error: UNC at LBA = 0x01b3fd5d = 28573021

commands leading to the command that caused the error were:

cr	fr	sc	sn	cl	ch	dh	dc	powered_up_time	command/feature_name
----	----	----	----	----	----	----	----	-----------------	----------------------

42	00	00	5d	fd	b3	40	00	15:31:06.644	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

42	00	01	5c	fd	b3	40	00	15:31:06.403	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

61	01	00	5c	fd	b3	40	00	15:31:06.403	WRITE FPDMA QUEUED
----	----	----	----	----	----	----	----	--------------	--------------------

42	00	00	5c	fd	b3	40	00	15:31:06.228	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

42	00	01	5b	fd	b3	40	00	15:31:06.041	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

error 11742 occurred at disk power-on lifetime: 34061 hours (1419 days + 5 hours)
when the command that caused the error occurred, the device was active or idle.

after command completion occurred, registers were:

er st sc sn cl ch dh

-- -- -- -- --

40 51 00 5c fd b3 01 error: UNC at LBA = 0x01b3fd5c = 28573020

commands leading to the command that caused the error were:

cr	fr	sc	sn	cl	ch	dh	dc	powered_up_time	command/feature_name
----	----	----	----	----	----	----	----	-----------------	----------------------

42	00	00	5c	fd	b3	40	00	15:31:06.228	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

42	00	01	5b	fd	b3	40	00	15:31:06.041	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

61	01	00	5b	fd	b3	40	00	15:31:06.041	WRITE FPDMA QUEUED
----	----	----	----	----	----	----	----	--------------	--------------------

61	18	00	00	db	45	40	00	15:31:05.988	WRITE FPDMA QUEUED
----	----	----	----	----	----	----	----	--------------	--------------------

42	00	00	5b	fd	b3	40	00	15:31:05.844	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

error 11741 occurred at disk power-on lifetime: 34061 hours (1419 days + 5 hours)
when the command that caused the error occurred, the device was active or idle.

after command completion occurred, registers were:

er st sc sn cl ch dh

-- -- -- -- --

40 51 00 5b fd b3 01 error: UNC at LBA = 0x01b3fd5b = 28573019

commands leading to the command that caused the error were:

cr	fr	sc	sn	cl	ch	dh	dc	powered_up_time	command/feature_name
----	----	----	----	----	----	----	----	-----------------	----------------------

42	00	00	5b	fd	b3	40	00	15:31:05.844	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

42	00	01	5a	fd	b3	40	00	15:31:05.671	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

61	01	00	5a	fd	b3	40	00	15:31:05.671	WRITE FPDMA QUEUED
----	----	----	----	----	----	----	----	--------------	--------------------

42	00	00	5a	fd	b3	40	00	15:31:05.519	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

42	00	01	59	fd	b3	40	00	15:31:05.350	READ VERIFY SECTOR(S) EXT
----	----	----	----	----	----	----	----	--------------	---------------------------

smart self-test log structure revision number 1

no self-tests have been logged. [to run self-tests, use: smartctl -t]

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
------	---------	---------	---------------------

1	0	0	not_testing
---	---	---	-------------

2	0	0	not_testing
---	---	---	-------------

3	0	0	not_testing
---	---	---	-------------


4	0	0	not_testing
---	---	---	-------------

5	0	0	not_testing
---	---	---	-------------

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.

if selective self-test is pending on power-up, resume after 0 minute delay.



Model: HGST HTS721010A9

S/N: JR10044M032DTN

Disk Erasure Report

Page 5 - Smart Data

