



Model: SEAGATE ST9500620SS
S/N: 9XF0BJKR



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST9500620SS**

Serial: **9XF0BJKR**

Size(Apparent): **500 GB, 500107862016 bytes**

Bus: **SAS**

Size(Real): **500 GB, 500107862016 bytes**

Disk Erasure Details

Start time: **2026/01/22 13:23:25**

End time: **2026/01/22 13:25:04**

Duration: **00:01:39**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **5734400000, (1.14%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/1/0**

Throughput: **57 MB/sec**


Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST9500620SS

S/N: 9XF0BJKR

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST9500620SS
revision: AS02
compliance: SPC-3
rotation rate: 7200 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500347354b7
serial number: 9XF0BJKR
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Jan 22 13:25:06 2026 GMT
device is not ready (e.g. spun down, busy)
a mandatory smart command failed: exiting. To continue, add one or more '-T permissive' options.