



Model: FUJITSU MBA3147RC

S/N: BJA3P9C0J3HL



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **FUJITSU MBA3147RC**

Serial: **BJA3P9C0J3HL**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2026/01/22 13:17:48**

End time: **2026/01/22 14:36:54**

Duration: **01:19:06**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **92 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: FUJITSU MBA3147RC

S/N: BJA3P9C0J3HL



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor: FUJITSU
product: MBA3147RC
revision: D306
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
logical unit id: 0x500000e113a00d90
serial number: BJA3P9C0J3HL
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Jan 22 14:36:56 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ====
smart health status: OK
```

```
current drive temperature: 33 C
drive trip temperature: 65 C
```

```
accumulated power on time, hours:minutes 127638:14
manufactured in week 52 of year 2009
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 25
elements in grown defect list: 0
```

```
error counter log:
      errors corrected by          total  correction    gigabytes    total
      ecc      rereads/  errors    algorithm  processed
      fast | delayed  rewrites  corrected  invocations  [10^9 bytes]  uncorrected
read:      0      106      106      106      121      224719.137      0
write:     0       59       59       59       70      152709.366      0
verify:    0       48       48       48       57      111745.165      0
```

```
non-medium error count: 28
```

```
smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description      number      (hours)
# 1  background long  completed      -          0      - [- - -]
# 2  background short completed      -          0      - [- - -]
```

```
long (extended) self-test duration: 1456 seconds [24.3 minutes]
```