



Model: TOSHIBA AL13SEB300

S/N: Y2J0A08UFRD6

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **TOSHIBA AL13SEB300**

Serial: **Y2J0A08UFRD6**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2026/01/22 13:23:19**

End time: **2026/01/22 17:09:11**

Duration: **03:45:52**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **66 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA AL13SEB300

S/N: Y2J0A08UFRD6

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA
product: AL13SEB300
revision: DE11
compliance: SPC-4
user capacity: 300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000394681a25f0
serial number: Y2J0A08UFRD6
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Jan 22 17:09:12 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 30 C
drive trip temperature: 65 C

accumulated power on time, hours:minutes 84443:55
manufactured in week 47 of year 2012
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 10
specified load-unload count over device lifetime: 200000
accumulated load-unload cycles: 450
elements in grown defect list: 0

error counter log:

	errors corrected by		total	correction	gigabytes	total
	ecc	rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	invocations	[10 ⁹ bytes]	errors
read:	0	15904	15907	282640	2632123.028	3
write:	0	379251	379251	411885	702926.455	0
verify:	0	285	286	2299	142236.246	1

non-medium error count: 29

no self-tests have been logged