



Model: HITACHI HUC106060CSS600

S/N: PPX4B26D



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **HITACHI HUC106060CSS600**

Serial: **PPX4B26D**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/22 13:23:29**

End time: **2026/01/22 17:30:16**

Duration: **04:06:47**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **121 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: HITACHI HUC106060CSS600
S/N: PPX4B26D



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor: HITACHI
product: HUC106060CSS600
revision: A440
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000cca02178a834
serial number: PPX4B26D
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Jan 22 17:30:18 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ====
smart health status: FIRMWARE IMPENDING FAILURE TOO MANY BLOCK REASSIGNS [asc=5d, ascq=64]
```

```
current drive temperature: 31 C
drive trip temperature: 85 C
```

```
accumulated power on time, hours:minutes 50608:28
manufactured in week 42 of year 2012
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 25
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 4559
elements in grown defect list: 6600
```

```
vendor (seagate cache) information
blocks sent to initiator = 159684903011614720
```

```
error counter log:
      errors corrected by      total      correction      gigabytes      total
      ecc      rereads/      errors      algorithm      processed      uncorrected
      fast | delayed      rewrites      corrected      invocations      [10^9 bytes]      errors
read:  5852993200      8786676      0      5861779876      52260481      272078.461      23600
write:      0      697182      0      697182      708383      264999.888      0
verify: 4160909358      30019      0      4160939377      1782028      90619.215      11043
```

```
non-medium error count:      0
```

```
no self-tests have been logged
```