



Model: SEAGATE ST300MP0026

S/N: WAE0BJQE

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST300MP0026**

Serial: **WAE0BJQE**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2026/01/22 17:14:55**

End time: **2026/01/22 19:40:09**

Duration: **02:25:14**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **103 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST300MP0026

S/N: WAE0BJQE

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST300MP0026
revision: KT3A
compliance: SPC-4
user capacity: 300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
lu is fully provisioned
rotation rate: 15000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c500b75403fb
serial number: WAE0BJQE
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Jan 22 19:40:11 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned = 3
power on minutes since format <not available>
current drive temperature: 38 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 26249:22
manufactured in week 03 of year 2018
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 32
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 1121
elements in grown defect list: 3

vendor (seagate cache) information

blocks sent to initiator = 1728611807
blocks received from initiator = 3816954553
blocks read from cache and sent to initiator = 1548418938
number of read and write commands whose size <= segment size = 378581393
number of read and write commands whose size > segment size = 208

vendor (seagate/hitachi) factory information


number of hours powered up = 26249.37
number of minutes until next internal smart test = 34

error counter log:

	errors corrected by ecc	fast delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	3201472666	2	0	3201472668	2	160245.904	0
write:	0	0	0	0	0	58294.726	0
verify:	2800795844	3	0	2800795847	3	48357.593	0

non-medium error count: 244

smart self-test log



Model: SEAGATE ST300MP0026
S/N: WAE0BJQE

Disk Erasure Report

Page 3 - Smart Data



num	test	status	segment	lifetime	lba_first_err	[sk	asc	asq]
	description		number	(hours)				
# 1	reserved(7)	completed	64	3	-	[-	-	-]
# 2	background short	completed	96	1	-	[-	-	-]

long (extended) self-test duration: 1800 seconds [30.0 minutes]