

Model: **SEAGATE ST31000424SS**

S/N: **9WK21ETW**



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST31000424SS**

Serial: **9WK21ETW**

Size(Apparent): **1000 GB, 1000204886016 bytes**

Bus: **SAS**

Size(Real): **1000 GB, 1000204886016 bytes**

Disk Erasure Details

Start time: **2026/01/22 13:18:15**

End time: **2026/01/22 20:58:44**

Duration: **07:40:29**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **1000204886016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **108 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST31000424SS

S/N: 9WK21ETW



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor:           SEAGATE
product:          ST31000424SS
revision:         KS68
compliance:       SPC-3
user capacity:    1,000,204,886,016 bytes [1.00 TB]
logical block size: 512 bytes
rotation rate:    7200 rpm
form factor:      3.5 inches
logical unit id: 0x5000c500215b121b
serial number:    9WK21ETW
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Thu Jan 22 20:58:46 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ====
smart health status: OK
```

```
current drive temperature:    30 C
drive trip temperature:       68 C
```

```
accumulated power on time, hours:minutes 2837:53
manufactured in week 42 of year 2010
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 39
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 39
elements in grown defect list: 0
```

```
vendor (seagate cache) information
blocks sent to initiator = 3238587061
blocks received from initiator = 1526423051
blocks read from cache and sent to initiator = 23834367
number of read and write commands whose size <= segment size = 360240546
number of read and write commands whose size > segment size = 0
```


```
vendor (seagate/hitachi) factory information
number of hours powered up = 2837.88
number of minutes until next internal smart test = 59
```

```
error counter log:
      errors corrected by          total  correction  gigabytes  total
      ecc      rereads/  errors  algorithm  processed  uncorrected
      fast | delayed  rewrites  corrected  invocations  [10^9 bytes]  errors
read:  427038447      1      0  427038448  427038448      1454.363      0
write:     0      0      0      0      0      5348.279      0
verify: 2799406680    200      0  2799406880  2799406880      315544.587      0
```

```
non-medium error count: 852
```

```
smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number   (hours)
# 1  background  long  completed          16      4          - [- - -]
# 2  background  long  completed          16      1          - [- - -]
# 3  background  short  completed          16      1          - [- - -]
```

```
long (extended) self-test duration: 11100 seconds [185.0 minutes]
```



Model: SEAGATE ST31000424SS

S/N: 9WK21ETW

Disk Erasure Report

Page 3 - Smart Data

