

Model: TOSHIBA AL14SEB060N

S/N: 76T0A0M1F08C

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **TOSHIBA AL14SEB060N**

Serial: **76T0A0M1F08C**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/22 17:15:06**

End time: **2026/01/22 22:05:35**

Duration: **04:50:29**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **103 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA AL14SEB060N

S/N: 76T0A0M1F08C

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA
product: AL14SEB060N
revision: DM05
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000039728582de5
serial number: 76T0A0M1F08C
device type: disk
transport protocol: SAS (SPL-3)
local time is: Thu Jan 22 22:05:44 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 31 C
drive trip temperature: 65 C

accumulated power on time, hours:minutes 70044:07
manufactured in week 30 of year 2016
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 27
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 122015
elements in grown defect list: 0

error counter log:

	errors corrected by			total	correction	gigabytes	total
	ecc		rereads/	errors	algorithm	processed	uncorrected
	fast	delayed	rewrites	corrected	invocations	[10^9 bytes]	errors
read:	0	83131	83131	83131	1733134	2038614.019	0
write:	0	6	6	6	7	10159.659	0
verify:	0	0	0	0	0	250269.231	0

non-medium error count: 26

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
			number	(hours)		
# 1	background short	completed	80	3	-	[- - -]
# 2	reserved(7)	completed	64	3	-	[- - -]

long (extended) self-test duration: 4107 seconds [68.5 minutes]