

Model: **SEAGATE ST900MM0006**

S/N: **S0N2N6MG**



## Disk Erasure Report

Page 1 - Erasure Status

### Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

### Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

### Disk Information

Make/Model: **SEAGATE ST900MM0006**

Serial: **S0N2N6MG**

Size(Apparent): **900 GB, 900185481216 bytes**

Bus: **SAS**

Size(Real): **900 GB, 900185481216 bytes**

### Disk Erasure Details

Start time: **2026/01/22 17:46:28**

End time: **2026/01/22 23:57:44**

Duration: **06:11:16**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **900185481216, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **121 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

\* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST900MM0006

S/N: S0N2N6MG



## Disk Erasure Report

Page 2 - Smart Data

---

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor:           SEAGATE
product:          ST900MM0006
revision:         LS0C
compliance:       SPC-4
user capacity:    900,185,481,216 bytes [900 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate:    10000 rpm
form factor:      2.5 inches
logical unit id:  0x5000c5007de2a453
serial number:    S0N2N6MG
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Thu Jan 22 23:57:45 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

==== start of read smart data section ====
smart health status: OK

current drive temperature:      30 C
drive trip temperature:         60 C

accumulated power on time, hours:minutes 15708:25
manufactured in week 42 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 35
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 11608
elements in grown defect list: 0


vendor (seagate cache) information
blocks sent to initiator = 3669883771
blocks received from initiator = 3715488094
blocks read from cache and sent to initiator = 2601129871
number of read and write commands whose size <= segment size = 1236542350
number of read and write commands whose size > segment size = 15

vendor (seagate/hitachi) factory information
number of hours powered up = 15708.42
number of minutes until next internal smart test = 0

error counter log:
      errors corrected by          total  correction  gigabytes  total
      ecc      rereads/  errors  algorithm  processed  [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:  775606979      0        0  775606979          0  225963.939      0
write:        0        0        11        11          11  125869.277      0
verify: 3834985877      1        0  3834985878          1  499393.692      0

non-medium error count: 11

smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number      (hours)
# 1  background short completed        64        3          - [- - -]
# 2  reserved(7)  completed        48        3          - [- - -]
# 3  background short completed        64        1          - [- - -]
```



**Model: SEAGATE ST900MM0006**

**S/N: S0N2N6MG**

## Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 5616 seconds [93.6 minutes]