



Model: WD WD2000FYYG

S/N: WMAWP0145762



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WD WD2000FYYG**

Serial: **WMAWP0145762**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

Disk Erasure Details

Start time: **2026/01/22 13:18:03**

End time: **2026/01/23 07:14:21**

Duration: **17:56:18**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **92 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD2000FYYG

S/N: WMAWP0145762



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor: WD
product: WD2000FYYG
revision: D1B3
compliance: SPC-4
user capacity: 2,000,398,934,016 bytes [2.00 TB]
logical block size: 512 bytes
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x50014ee3aab836fc
serial number: WMAWP0145762
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Jan 23 07:14:22 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ====
smart health status: OK
```

```
current drive temperature: 37 C
drive trip temperature: 64 C
```

```
accumulated power on time, hours:minutes 107146:10
manufactured in week of year 2010
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 53
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 53
elements in grown defect list: 0
```

```
error counter log:
      errors corrected by          total  correction  gigabytes  total
      ecc          rereads/  errors  algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:  51505351      852      0  51506203      3869          0.603          0
write: 2889  6581411      0  6584300  6581412          3.371          0
verify: 66609      256      0  66865      262          0.034          0
```

```
non-medium error count: 3490585
```

```
smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number    (hours)
# 1  background long  completed      32       27          - [- - -]
# 2  background long  aborted (device reset ?) 32       10          - [- - -]
# 3  background short completed      32       10          - [- - -]
```

```
long (extended) self-test duration: 64583 seconds [1076.4 minutes]
```