



Model: SEAGATE ST3300657SS-H

S/N: 6SJ1C61H



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-3**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST3300657SS-H**

Serial: **6SJ1C61H**

Size(Apparent): **146 GB, 146815733760 bytes**

Bus: **SAS**

Size(Real): **146 GB, 146815733760 bytes**

Disk Erasure Details

Start time: **2026/01/23 08:00:16**

End time: **2026/01/23 08:39:12**

Duration: **00:38:56**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **146815733760, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/0**

Throughput: **125 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



**Model: SEAGATE ST3300657SS-H
S/N: 6SJ1C61H**



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor: SEAGATE
product: ST3300657SS-H
revision: EH02
compliance: SPC-3
user capacity: 146,815,733,760 bytes [146 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 3.5 inches
logical unit id: 0x5000c50039c9e31f
serial number: 6SJ1C61H
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Jan 23 08:39:14 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

==== start of read smart data section ===
smart health status: FAILURE PREDICTION THRESHOLD EXCEEDED: ascq=0x5 [asc=5d, ascq=5]

current drive temperature: 35 C
drive trip temperature: 68 C

accumulated power on time, hours:minutes 13241:29
elements in grown defect list: 2007

vendor (seagate cache) information
blocks sent to initiator = 209625776
blocks received from initiator = 4201788910
blocks read from cache and sent to initiator = 980705880
number of read and write commands whose size <= segment size = 1424020307
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information
number of hours powered up = 13241.48
number of minutes until next internal smart test = 59

error counter log:
      errors corrected by          total      correction      gigabytes      total
      ecc          rereads/    errors    algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed    rewrites  corrected  invocations
read:  2306568994      148        0  2306569142  2306569154    70652.096          12
write:     0        0       16        16        49  154143.914          28
verify: 2436729289     233        0  2436729522  2436729857    89155.001          267

non-medium error count: 600

smart self-test log
num  test          status          segment      lifetime  lba_first_err [sk asc asq]
     description          number      (hours)
# 1  background long  completed          16          2          - [- - -]
# 2  background long  completed          16          1          - [- - -]
# 3  background short completed          16          1          - [- - -]

long (extended) self-test duration: 3200 seconds [53.3 minutes]
```