



Model: SEAGATE ST4000NM0125

S/N: ZC1A0ATL0000C9240CZB



## Disk Erasure Report

Page 1 - Erasure Status

### Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

### Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

### Disk Information

Make/Model: **SEAGATE ST4000NM0125**

Serial: **ZC1A0ATL0000C9240CZB**

Size(Apparent): **4000 GB, 4000787030016 bytes**

Bus: **SAS**

Size(Real): **4000 GB, 4000787030016 bytes**

### Disk Erasure Details

Start time: **2026/01/22 13:18:32**

End time: **2026/01/23 09:01:52**

Duration: **19:43:20**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

\*Bytes Erased: **4000787030016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **169 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

\* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



**Model: SEAGATE ST4000NM0125**

**S/N: ZC1A0ATL0000C9240CZB**

# Disk Erasure Report

Page 2 - Smart Data



```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor:           SEAGATE
product:          ST4000NM0125
revision:         E003
compliance:       SPC-4
user capacity:    4,000,787,030,016 bytes [4.00 TB]
logical block size: 512 bytes
physical block size: 4096 bytes
lu is fully provisioned
rotation rate:    7200 rpm
form factor:      3.5 inches
logical unit id: 0x5000c500a7a97c7b
serial number:    ZC1A0ATL0000C9240CZB
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Fri Jan 23 09:01:53 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled
```

```
==== start of read smart data section ===
smart health status: OK
```

```
grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned <not available>
power on minutes since format <not available>
current drive temperature: 32 C
drive trip temperature: 60 C
```

```
accumulated power on time, hours:minutes 15505:59
manufactured in week 03 of year 2019
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 215
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 11514
elements in grown defect list: 0
```

```
vendor (seagate cache) information
blocks sent to initiator = 3520793184
blocks received from initiator = 2743211872
blocks read from cache and sent to initiator = 927472
number of read and write commands whose size <= segment size = 46590
number of read and write commands whose size > segment size = 1333
```

```
vendor (seagate/hitachi) factory information
number of hours powered up = 15505.98
number of minutes until next internal smart test = 53
```

```
error counter log:
      errors corrected by          total  correction      gigabytes      total
      ecc          rereads/  errors  algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations      0           0  errors
read:  1953505469      0          0  1953505469      0      4001.669      0
write:     0          0          0          0          0      8001.614      0
```

```
non-medium error count: 1
```

```
[gltsd (global logging target save disable) set. enable save with '-s on']
no self-tests have been logged
```



**Model: SEAGATE ST4000NM0125**

**S/N: ZC1A0ATL0000C9240CZB**

## Disk Erasure Report

Page 3 - Smart Data

