



Model: SEAGATE ST300MP0106

S/N: SAE00WKA0000E715EWMG

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **SEAGATE ST300MP0106**

Serial: **SAE00WKA0000E715EWMG**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2026/01/23 08:08:43**

End time: **2026/01/23 09:37:51**

Duration: **01:29:08**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **168 MB/sec**


Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST300MP0106

S/N: SAE00WKA0000E715EWMG

Disk Erasure Report

Page 2 - Smart Data



```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor:           SEAGATE
product:          ST300MP0106
revision:         C002
compliance:       SPC-4
user capacity:    300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
physical block size: 4096 bytes
lu is fully provisioned
rotation rate:    15052 rpm
form factor:      2.5 inches
logical unit id:  0x5000c50099a0eb3f
serial number:    SAE00WKA0000E715EWMG
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Fri Jan 23 09:37:53 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled
```

```
==== start of read smart data section ====
smart health status: OK
```

```
grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned <not available>
power on minutes since format <not available>
current drive temperature: 39 C
drive trip temperature: 60 C
```

```
accumulated power on time, hours:minutes 59133:27
manufactured in week 49 of year 2016
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 24
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 2481
elements in grown defect list: 0
```

```
vendor (seagate cache) information
blocks sent to initiator = 586122048
blocks received from initiator = 1171906392
blocks read from cache and sent to initiator = 55769
number of read and write commands whose size <= segment size = 3776
number of read and write commands whose size > segment size = 338
```

```
vendor (seagate/hitachi) factory information
number of hours powered up = 59133.45
number of minutes until next internal smart test = 30
```

```
error counter log:
      errors corrected by          total  correction  gigabytes  total
      ecc          rereads/  errors  algorithm  processed  uncorrected
      fast | delayed  rewrites  corrected  invocations  [10^9 bytes]  errors
read:  73268220      0        0  73268220        0      300.094        0
write:     0        0        0        0        0      600.061        0
```

```
non-medium error count: 0
```

```
[gltsd (global logging target save disable) set. enable save with '-s on']
no self-tests have been logged
```



Model: SEAGATE ST300MP0106
S/N: SAE00WKA0000E715EWMG

Disk Erasure Report

Page 3 - Smart Data

