



Model: TOSHIBA MK3001GRRB

S/N: Z3R0A1NDFQ85



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **TOSHIBA MK3001GRRB**

Serial: **Z3R0A1NDFQ85**

Size(Apparent): **300 GB, 300000000000 bytes**

Bus: **SAS**

Size(Real): **300 GB, 300000000000 bytes**

Disk Erasure Details

Start time: **2026/01/23 08:08:47**

End time: **2026/01/23 10:07:56**

Duration: **01:59:09**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **300000000000, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **125 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA MK3001GRRB

S/N: Z3R0A1NDFQ85



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor: TOSHIBA
product: MK3001GRRB
revision: DB08
compliance: SPC-4
user capacity: 300,000,000,000 bytes [300 GB]
logical block size: 512 bytes
rotation rate: 15000 rpm
form factor: 2.5 inches
logical unit id: 0x5000039538400260
serial number: Z3R0A1NDFQ85
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Jan 23 10:07:57 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ====
smart health status: OK
```

```
current drive temperature: 30 C
drive trip temperature: 65 C
```

```
accumulated power on time, hours:minutes 90439:29
manufactured in week 52 of year 2013
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 34
specified load-unload count over device lifetime: 200000
accumulated load-unload cycles: 8951
elements in grown defect list: 80
```

```
error counter log:
      errors corrected by          total  correction      gigabytes      total
      ecc          rereads/  errors  algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:      0      638      639      638      18469    4721467.786      1
write:     0       90       91       90      1114    731352.247      1
verify:    0        1        2        1        82    160998.608      1
```

```
non-medium error count: 47
```

```
smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number    (hours)
# 1  background short completed        48        2          - [- - -]
# 2  background long  completed        48        2          - [- - -]
# 3  background short completed        48        2          - [- - -]
```

```
long (extended) self-test duration: 1725 seconds [28.8 minutes]
```