



Model: **TOSHIBA AL15SEB060NY**

S/N: **88K0A2EDFQWF**



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **TOSHIBA AL15SEB060NY**

Serial: **88K0A2EDFQWF**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/23 08:06:06**

End time: **2026/01/23 10:54:25**

Duration: **02:48:19**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **178 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: TOSHIBA AL15SEB060NY

S/N: 88K0A2EDFQWF



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor: TOSHIBA
product: AL15SEB060NY
revision: EF03
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000398d862779d
serial number: 88K0A2EDFQWF
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Jan 23 10:54:26 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ===
smart health status: OK
```

```
current drive temperature: 29 C
drive trip temperature: 65 C
```

```
accumulated power on time, hours:minutes 61728:03
manufactured in week 34 of year 2018
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 22
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 22
elements in grown defect list: 0
```

```
error counter log:
      errors corrected by          total  correction  gigabytes  total
      ecc          rereads/  errors  algorithm  processed  [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:      0      628      628      628      10241  3356001.477      0
write:     0       9       9       9       9  243504.615      0
verify:    0       0       0       0       0  220870.515      0
```

```
non-medium error count: 21
```

```
smart self-test log
num test          status          segment  lifetime  lba_first_err [sk asc asq]
      description          number  (hours)
# 1 reserved(7)  completed          64        3          - [- - -]
# 2 background short completed          -         1          - [- - -]
```

long (extended) self-test duration: 3116 seconds [51.9 minutes]