



Model: WD WD6001BKHG

S/N: WXB1E92PRF36



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **WD WD6001BKHG**

Serial: **WXB1E92PRF36**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/23 08:05:49**

End time: **2026/01/23 11:11:09**

Duration: **03:05:20**

Status: **FAILED**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **0/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **1/0/0**

Throughput: **115 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: WD WD6001BKHG

S/N: WXB1E92PRF36



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.22.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor: WD
product: WD6001BKHG
revision: D1S6
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000c0f02088b50
serial number: WXB1E92PRF36
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Jan 23 11:11:11 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported
```

```
==== start of read smart data section ===
smart health status: OK
```

```
current drive temperature: 31 C
drive trip temperature: 64 C
```

```
accumulated power on time, hours:minutes 107838:48
manufactured in week 05 of year 2013
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 46
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 43000
elements in grown defect list: 42
```

```
error counter log:
      errors corrected by          total  correction  gigabytes  total
      ecc          rereads/  errors  algorithm  processed  uncorrected
      fast | delayed  rewrites  corrected  invocations [10^9 bytes]  errors
read: 1058458756  30143   245188  1058488899    30310    50792.157    167
write: 4294967295  35010  3127337  4294967295    35013   445483.049     0
verify: 1396798   57628  1914372  1454426     61123    4548.883    3474
```

```
non-medium error count: 268
```

```
smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number    (hours)
# 1  background long  completed      32  12263      - [-] - [-]
# 2  background short aborted (by user command) 32  12262      - [-] - [-]
# 3  background short completed      32      3      - [-] - [-]
# 4  background long  aborted (by user command) 32      3      - [-] - [-]
# 5  background short aborted (by user command) 32      1      - [-] - [-]
```

```
long (extended) self-test duration: 4144 seconds [69.1 minutes]
```