



Model: TOSHIBA AL15SEB060NY

S/N: 88K0A2CAFQWF

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-6**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **TOSHIBA AL15SEB060NY**

Serial: **88K0A2CAFQWF**

Size(Apparent): **600 GB, 600127266816 bytes**

Bus: **SAS**

Size(Real): **600 GB, 600127266816 bytes**

Disk Erasure Details

Start time: **2026/01/23 08:07:13**

End time: **2026/01/23 12:02:04**

Duration: **03:54:51**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **600127266816, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **127 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: TOSHIBA AL15SEB060NY
S/N: 88K0A2CAFQWF



Disk Erasure Report

Page 2 - Smart Data

smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: TOSHIBA
product: AL15SEB060NY
revision: EF03
compliance: SPC-4
user capacity: 600,127,266,816 bytes [600 GB]
logical block size: 512 bytes
formatted with type 2 protection
8 bytes of protection information per logical block
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x50000398d8626c41
serial number: 88K0A2CAFQWF
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Jan 23 12:02:05 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===
smart health status: OK

current drive temperature: 32 C
drive trip temperature: 65 C

accumulated power on time, hours:minutes 61728:59
manufactured in week 34 of year 2018
specified cycle count over device lifetime: 50000
accumulated start-stop cycles: 23
specified load-unload count over device lifetime: 600000
accumulated load-unload cycles: 23
elements in grown defect list: 0

error counter log:

	errors corrected by		total errors corrected	correction algorithm invocations	gigabytes processed [10 ⁹ bytes]	total uncorrected errors
	ecc	rereads/ rewrites				
	fast	delayed				
read:	0	14	14	32	3011218.130	0
write:	0	36	36	36	219821.498	0
verify:	0	0	0	0	220870.383	0

non-medium error count: 21

smart self-test log

num	test	status	segment number	lifetime (hours)	lba_first_err	[sk asc asq]
	description					
# 1	reserved(7)	completed	64	3	-	[- - -]
# 2	background short	completed	-	1	-	[- - -]

long (extended) self-test duration: 3116 seconds [51.9 minutes]