



Model: SEAGATE ST900MM0006

S/N: S0N2N7CC

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **SEAGATE ST900MM0006**

Serial: **S0N2N7CC**

Size(Apparent): **900 GB, 900185481216 bytes**

Bus: **SAS**

Size(Real): **900 GB, 900185481216 bytes**

Disk Erasure Details

Start time: **2026/01/23 08:10:26**

End time: **2026/01/23 14:05:19**

Duration: **05:54:53**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **900185481216, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **126 MB/sec**


Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST900MM0006

S/N: S0N2N7CC

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST900MM0006
revision: LS0C
compliance: SPC-4
user capacity: 900,185,481,216 bytes [900 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 10000 rpm
form factor: 2.5 inches
logical unit id: 0x5000c5007de267bf
serial number: S0N2N7CC
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Jan 23 14:05:21 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

=== start of read smart data section ===

smart health status: OK

current drive temperature: 37 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 15705:42
manufactured in week 42 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 35
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 11595
elements in grown defect list: 0

vendor (seagate cache) information

blocks sent to initiator = 1877572898
blocks received from initiator = 3239402059
blocks read from cache and sent to initiator = 2573752041
number of read and write commands whose size <= segment size = 1232567482
number of read and write commands whose size > segment size = 11

vendor (seagate/hitachi) factory information

number of hours powered up = 15705.70
number of minutes until next internal smart test = 14

error counter log:

	errors corrected by	total	correction	gigabytes	total
	ecc	errors	algorithm	processed	uncorrected
	fast delayed	rewrites	corrected	invocations	[10^9 bytes]
read:	3947034316	0	3947034316	0	225050.969
write:	0	0	6	7	123279.018
verify:	901726360	0	901726360	0	499388.999

non-medium error count: 12

smart self-test log

num	test	status	segment	lifetime	lba_first_err	[sk asc asq]
	description		number	(hours)		
# 1	background short	completed	64	3	-	[- - -]
# 2	reserved(7)	completed	48	3	-	[- - -]
# 3	background short	completed	64	1	-	[- - -]



Model: SEAGATE ST900MM0006
S/N: S0N2N7CC

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 5616 seconds [93.6 minutes]