



Model: SEAGATE ST900MM0006

S/N: S0N2N5MA



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **Not Applicable (BN)**

Business Address: **Not Applicable (BA)**

Contact Name: **Not Applicable (BCN)**

Contact Phone: **Not Applicable (BCP)**

Customer Details

Name: **Not Applicable (CN)**

Address: **Not Applicable (CA)**

Contact Name: **Not Applicable (CCN)**

Contact Phone: **Not Applicable (CP)**

Disk Information

Make/Model: **SEAGATE ST900MM0006**

Serial: **S0N2N5MA**

Size(Apparent): **900 GB, 900185481216 bytes**

Bus: **SAS**

Size(Real): **900 GB, 900185481216 bytes**

Disk Erasure Details

Start time: **2026/01/23 08:09:46**

End time: **2026/01/23 14:10:40**

Duration: **06:00:54**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **900185481216, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **124 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Not Applicable (OTN)**



Model: SEAGATE ST900MM0006

S/N: S0N2N5MA



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor:           SEAGATE
product:          ST900MM0006
revision:         LS0C
compliance:       SPC-4
user capacity:    900,185,481,216 bytes [900 GB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate:    10000 rpm
form factor:      2.5 inches
logical unit id: 0x5000c5007de2f557
serial number:    S0N2N5MA
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Fri Jan 23 14:10:41 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Disabled or Not Supported

==== start of read smart data section ===
smart health status: OK

current drive temperature:      39 C
drive trip temperature:         60 C

accumulated power on time, hours:minutes 15707:09
manufactured in week 42 of year 2014
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 35
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 11609
elements in grown defect list: 0


vendor (seagate cache) information
blocks sent to initiator = 1621498290
blocks received from initiator = 4205151523
blocks read from cache and sent to initiator = 981563728
number of read and write commands whose size <= segment size = 1203844474
number of read and write commands whose size > segment size = 20

vendor (seagate/hitachi) factory information
number of hours powered up = 15707.15
number of minutes until next internal smart test = 8

error counter log:
      errors corrected by          total  correction      gigabytes      total
      ecc      rereads/  errors   algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations      errors
read:  1690976426      0      0  1690976426          0  178743.957      0
write:      0      0    301      301      301  124610.862      0
verify: 2163720228      0      0  2163720228          0  499385.413      0

non-medium error count:      0

smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
      description          number   (hours)
# 1  background short completed      64        3          - [- - -]
# 2  reserved(7)  completed      48        3          - [- - -]
# 3  background short completed      64        1          - [- - -]
```



Model: SEAGATE ST900MM0006

S/N: S0N2N5MA

Disk Erasure Report

Page 3 - Smart Data



long (extended) self-test duration: 5616 seconds [93.6 minutes]