



Model: SEAGATE ST4000NM0025

S/N: ZC12EGJG0000R745NLMJ

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST4000NM0025**

Serial: **ZC12EGJG0000R745NLMJ**

Size(Apparent): **4000 GB, 4000787030016 bytes**

Bus: **SAS**

Size(Real): **4000 GB, 4000787030016 bytes**

Disk Erasure Details

Start time: **2026/01/22 18:13:01**

End time: **2026/01/23 16:52:14**

Duration: **22:39:13**

Status: **ERASED** **See Warning !**

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **4000787030016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **147 MB/sec**

Information: **Warning** **HPA/DCO data unavailable, can not determine hidden sector status.**

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST4000NM0025

S/N: ZC12EGJG0000R745NLMJ

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

vendor: SEAGATE
product: ST4000NM0025
revision: N002
compliance: SPC-4
user capacity: 4,000,787,030,016 bytes [4.00 TB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate: 7200 rpm
form factor: 3.5 inches
logical unit id: 0x5000c500942d49ef
serial number: ZC12EGJG0000R745NLMJ
device type: disk
transport protocol: SAS (SPL-3)
local time is: Fri Jan 23 16:52:15 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

=== start of read smart data section ===

smart health status: OK

grown defects during certification <not available>
total blocks reassigned during format <not available>
total new blocks reassigned = 0
power on minutes since format <not available>
current drive temperature: 35 C
drive trip temperature: 60 C

accumulated power on time, hours:minutes 53045:50
manufactured in week 24 of year 2017
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 91
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 213728
elements in grown defect list: 1

vendor (seagate cache) information

blocks sent to initiator = 3786160865
blocks received from initiator = 2743179948
blocks read from cache and sent to initiator = 985928
number of read and write commands whose size <= segment size = 329181
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information


number of hours powered up = 53045.83
number of minutes until next internal smart test = 59

error counter log:

	errors corrected by ecc	errors corrected by fast delayed	rereads/ rewrites	total errors corrected	correction algorithm invocations	gigabytes processed [10^9 bytes]	total uncorrected errors
read:	4838244	0	0	4838244	0	4137.538	0
write:	0	0	0	0	0	8001.631	0

non-medium error count: 3

[gltsd (global logging target save disable) set. enable save with '-s on']
no self-tests have been logged



Model: SEAGATE ST4000NM0025
S/N: ZC12EGJG0000R745NLMJ

Disk Erasure Report

Page 3 - Smart Data

