



Model: SEAGATE ST4000NM0023

S/N: Z1Z9WG4A0000R610Y4Z8



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **SEAGATE ST4000NM0023**

Serial: **Z1Z9WG4A0000R610Y4Z8**

Size(Apparent): **4000 GB, 4000787030016 bytes**

Bus: **SAS**

Size(Real): **4000 GB, 4000787030016 bytes**

Disk Erasure Details

Start time: **2026/01/22 18:12:49**

End time: **2026/01/23 19:15:47**

Duration: **25:02:58**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **4000787030016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **133 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: SEAGATE ST4000NM0023

S/N: Z1Z9WG4A0000R610Y4Z8



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ===
vendor:           SEAGATE
product:          ST4000NM0023
revision:         0004
compliance:       SPC-4
user capacity:    4,000,787,030,016 bytes [4.00 TB]
logical block size: 512 bytes
lu is fully provisioned
rotation rate:    7200 rpm
form factor:      3.5 inches
logical unit id: 0x5000c50084809d53
serial number:    Z1Z9WG4A0000R610Y4Z8
device type:      disk
transport protocol: SAS (SPL-3)
local time is:    Fri Jan 23 19:15:49 2026 GMT
smart support is: Available - device has SMART capability.
smart support is: Enabled
temperature warning: Enabled

==== start of read smart data section ===
smart health status: OK

current drive temperature:      36 C
drive trip temperature:         60 C

accumulated power on time, hours:minutes 60730:43
manufactured in week 43 of year 2015
specified cycle count over device lifetime: 10000
accumulated start-stop cycles: 106
specified load-unload count over device lifetime: 300000
accumulated load-unload cycles: 2630
elements in grown defect list: 0

vendor (seagate cache) information
blocks sent to initiator = 3519621748
blocks received from initiator = 2743183952
blocks read from cache and sent to initiator = 107848
number of read and write commands whose size <= segment size = 232070
number of read and write commands whose size > segment size = 0

vendor (seagate/hitachi) factory information
number of hours powered up = 60730.72
number of minutes until next internal smart test = 0

error counter log:
      errors corrected by          total    correction      gigabytes      total
      ecc      rereads/    errors    algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed   rewrites  corrected  invocations      errors
read:  3625973989      0        0  3625973989          0    2781.299          0
write:        0        0        0          0          0    8010.505          0

non-medium error count:      11

[gltsd (global logging target save disable) set. enable save with '-s on']
no self-tests have been logged
```