



Model: WD WD2000FYYG

S/N: WMAWP0187644



Disk Erasure Report

Page 1 - Erasure Status

Organisation Performing The Disk Erasure

Business Name: **GridJet**

Business Address:

Contact Name: **GDW-LDS-4**

Contact Phone:

Customer Details

Name: **Gridjet**

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: **WD WD2000FYYG**

Serial: **WMAWP0187644**

Size(Apparent): **2000 GB, 2000398934016 bytes**

Bus: **SAS**

Size(Real): **2000 GB, 2000398934016 bytes**

Disk Erasure Details

Start time: **2026/01/22 18:17:39**

End time: **2026/01/24 01:03:22**

Duration: **30:45:43**

Status: **ERASED** See Warning !

Method: **PRNG Stream**

PRNG algorithm: **XORshiro256**

Final Pass(Zeros/Ones/None): **Zeros**

Verify Pass(Last/All/None): **Verify Last**

*Bytes Erased: **2000398934016, (100.00%)**

Rounds(completed/requested): **1/1**

HPA/DCO: **Unknown**

HPA/DCO Size: **Unknown**

Errors(pass/sync/verify): **0/0/0**

Throughput: **54 MB/sec**

Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: **Auto Wipe**



Model: WD WD2000FYYG

S/N: WMAWP0187644



Disk Erasure Report

Page 2 - Smart Data

```
smartctl 7.2 2020-12-30 r5155 [x86_64-linux-5.14.0-503.23.1.el9_5.x86_64] (local build)
copyright (c) 2002-20, bruce allen, christian franke, www.smartmontools.org
```

```
==== start of information section ====
vendor:                  WD
product:                 WD2000FYYG
revision:                D1BC
compliance:              SPC-4
user capacity:           2,000,398,934,016 bytes [2.00 TB]
logical block size:      512 bytes
rotation rate:           7200 rpm
form factor:             3.5 inches
logical unit id:         0x50014ee3000f5ec4
serial number:            WMAWP0187644
device type:              disk
transport protocol:       SAS (SPL-3)
local time is:            Sat Jan 24 01:03:24 2026 GMT
smart support is:         Available - device has SMART capability.
smart support is:         Enabled
temperature warning:      Disabled or Not Supported
```

```
==== start of read smart data section ====
smart health status: OK
```

```
current drive temperature: 35 C
drive trip temperature: 64 C
```

```
accumulated power on time, hours:minutes 107066:09
manufactured in week of year 2010
specified cycle count over device lifetime: 1048576
accumulated start-stop cycles: 52
specified load-unload count over device lifetime: 1114112
accumulated load-unload cycles: 52
elements in grown defect list: 0
```

```
error counter log:
      errors corrected by          total  correction  gigabytes  total
      ecc          rereads/  errors  algorithm  processed [10^9 bytes]  uncorrected
      fast | delayed  rewrites  corrected  invocations
read:  51982159    3071      0  51985230    10832          0.851      0
write:  3260    7165164      0  7168424    7165164          3.670      0
verify: 145880     991      0  146871     1102          0.075      0
```

```
non-medium error count: 4438857
```

```
smart self-test log
num  test          status          segment  lifetime  lba_first_err [sk asc asq]
     description          number    (hours)
# 1  background long completed        32       27          - [- - -]
# 2  background long aborted (device reset ?) 32       10          - [- - -]
# 3  background short completed       32       10          - [- - -]
```

```
long (extended) self-test duration: 64583 seconds [1076.4 minutes]
```